

Data sheet for SIMOTICS S-1FK7



Figure similar

Article No. : 1FK7032-2AK71-1RA1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

| | |
|-----------------------|-------------------------|
| Rated speed (100 K) | 6,000 rpm |
| Number of poles | 6 |
| Rated torque (100 K) | 0.8 Nm |
| Rated current | 1.3 A |
| Static torque (60 K) | 0.95 Nm |
| Static torque (100 K) | 1.10 Nm |
| Stall current (60 K) | 1.40 A |
| Stall current (100 K) | 1.70 A |
| Moment of inertia | 0.650 kgcm ² |
| Efficiency | 88.0 % |

Physical constants

| | |
|-----------------------------|-------------------------------|
| Torque constant | 0.67 Nm/A |
| Voltage constant at 20° C | 45.0 V/1000*min ⁻¹ |
| Winding resistance at 20° C | 5.05 Ω |
| Rotating field inductance | 17.3 mH |
| Electrical time constant | 3.45 ms |
| Mechanical time constant | 2.20 ms |
| Thermal time constant | 25 min |
| Shaft torsional stiffness | 6,000 Nm/rad |
| Net weight of the motor | 2.7 kg |

Mechanical data

| | |
|--------------------------|---|
| Motor type | Permanent-magnet synchronous motor |
| Motor type | Compact |
| Shaft height | 36 |
| Cooling | Natural cooling |
| Radial runout tolerance | 0.035 mm |
| Concentricity tolerance | 0.08 mm |
| Axial runout tolerance | 0.08 mm |
| Vibration severity grade | Grade A |
| Connector size | 1 |
| Degree of protection | IP65 |
| Design acc. to Code I | IM B5 (IM V1, IM V3) |
| Temperature monitoring | Pt1000 temperature sensor |
| Electrical connectors | Connectors for signals and power rotatable |
| Color of the housing | Standard (Anthracite RAL 7016) |
| Holding brake | without holding brake |
| Shaft end | Feather key |
| Encoder system | Encoder AM20DQI: absolute encoder 20 bits (resolution 1048576, encoder-internal 512 S/R) + 12 bits multi-turn (traversing range 4096 revolutions) |

Optimum operating point

| | |
|---------------|-----------|
| Optimum speed | 6,000 rpm |
| Optimum power | 0.5 kW |

Limiting data

| | |
|-----------------------------------|------------|
| Max. permissible speed (mech.) | 10,000 rpm |
| Max. permissible speed (inverter) | 10,000 rpm |
| Maximum torque | 4.5 Nm |
| Maximum current | 7.0 A |

Recommended Motor Module

| | |
|--------------------------|---------|
| Rated inverter current | 3 A |
| Maximum inverter current | 9 A |
| Maximum torque | 4.50 Nm |

TURLL

YOUR GLOBAL AUTOMATION PARTNER

1FK7032-2AK71-1RA1

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

sales@turl.com | +852 6339 7344