

Data sheet for SIMOTICS S-1FK7

Article No. : 1FK7032-2AK71-1RH1-Z
N16

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :



Figure similar

Engineering data

Rated speed (100 K)	6,000 rpm
Number of poles	6
Rated torque (100 K)	0.8 Nm
Rated current	1.3 A
Static torque (60 K)	0.95 Nm
Static torque (100 K)	1.10 Nm
Stall current (60 K)	1.40 A
Stall current (100 K)	1.70 A
Moment of inertia	0.750 kgcm ²
Efficiency	88.0 %

Physical constants

Torque constant	0.67 Nm/A
Voltage constant at 20° C	45.0 V/1000*min ⁻¹
Winding resistance at 20° C	5.05 Ω
Rotating field inductance	17.3 mH
Electrical time constant	3.45 ms
Mechanical time constant	2.20 ms
Thermal time constant	25 min
Shaft torsional stiffness	4,100 Nm/rad
Net weight of the motor	3.1 kg

Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	36
Cooling	Natural cooling
Radial runout tolerance	0.035 mm
Concentricity tolerance	0.08 mm
Axial runout tolerance	0.08 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP65
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	Standard (Anthracite RAL 7016)
Holding brake	with holding brake
Shaft end	Plain shaft
Encoder system	Encoder AM20DQI with nickel-plated M17 round connector: absolute encoder 20 bits (resolution 1048576, encoder-internal 512 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)

Optimum operating point

Optimum speed	6,000 rpm
Optimum power	0.5 kW

Limiting data

Max. permissible speed (mech.)	10,000 rpm
Max. permissible speed (inverter)	10,000 rpm
Maximum torque	4.5 Nm
Maximum current	7.0 A

Holding brake

Holding brake version	Permanent-magnet brake
Holding torque	1.9 Nm
Power supply voltage	DC 24 V ± 10 %
Coil current	0.3 A
Opening time	50 ms
Closing time	30 ms
Highest braking work	40 J



Figure similar

Data sheet for SIMOTICS S-1FK7

Article No. : 1FK7032-2AK71-1RH1-Z
N16

Recommended Motor Module	
Rated inverter current	3 A
Maximum inverter current	9 A
Maximum torque	4.50 Nm
Special design	
N16	Nickel plated connectors and paint varnish for increased chemical resistance

TURLL

YOUR GLOBAL AUTOMATION PARTNER

1FK7032-2AK71-1RH1-ZN16

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

CHECK STOCK & PRICE



Need Assistance? Scan to Chat on WhatsApp

sales@turll.com | +852 6339 7344