



Data sheet for SIMOTICS S-1FK7



Figure similar

Article No. : 1FK7034-2AK71-1CG0-Z
Y84

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data	
Rated speed (100 K)	6,000 rpm
Number of poles	6
Rated torque (100 K)	1.0 Nm
Rated current	1.3 A
Static torque (60 K)	1.35 Nm
Static torque (100 K)	1.60 Nm
Stall current (60 K)	1.55 A
Stall current (100 K)	1.90 A
Moment of inertia	0.900 kgcm²
Efficiency	88.0 %

Physical constants	
Torque constant	0.84 Nm/A
Voltage constant at 20° C	55.0 V/1000*min ⁻¹
Winding resistance at 20° C	4.46 Ω
Rotating field inductance	17.2 mH
Electrical time constant	3.85 ms
Mechanical time constant	1.71 ms
Thermal time constant	30 min
Shaft torsional stiffness	5,300 Nm/rad
Net weight of the motor	3.5 kg

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	36
Cooling	Natural cooling
Radial runout tolerance	0.035 mm
Concentricity tolerance	0.08 mm
Axial runout tolerance	0.08 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP64
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	Standard (Anthracite RAL 7016)
Holding brake	without holding brake
Shaft end	Plain shaft
Encoder system	Encoder AM24DQI: absolute encoder 24 bits (resolution 16777216, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)

Optimum operating point	
Optimum speed	6,000 rpm
Optimum power	0.6 kW

Limiting data	
Max. permissible speed (mech.)	10,000 rpm
Max. permissible speed (inverter)	10,000 rpm
Maximum torque	6.5 Nm
Maximum current	8.0 A

Recommended Motor Module	
Rated inverter current	3 A
Maximum inverter current	9 A
Maximum torque	6.50 Nm

Special design	
Y84	Customer specifications on rating plate:

TURLL

YOUR GLOBAL AUTOMATION PARTNER

1FK7034-2AK71-1CG0-ZY84

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

CHECK STOCK & PRICE



Need Assistance? Scan to Chat on WhatsApp

sales@turll.com | +852 6339 7344