Global Automation Distributor | TURLL.com

SIEMENS

Data sheet for SIMOTICS S-1FK7 servo geared motor



Figure similar

Article No. : 1FK7034-2AK71-1RG1-Z
J15

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data	
Rated speed (100 K)	6,000 rpm
Number of poles	6
Rated torque (100 K)	1.0 Nm
Rated current	1.3 A
Static torque (60 K)	1.35 Nm
Static torque (100 K)	1.60 Nm
Stall current (60 K)	1.55 A
Stall current (100 K)	1.90 A
Moment of inertia	1.080 kgcm²

Physical constants	
Torque constant	0.84 Nm/A
Voltage constant at 20° C	55.0 V/1000*min⁻¹
Winding resistance at 20° C	4.46 Ω
Rotating field inductance	17.2 mH
Electrical time constant	3.85 ms
Mechanical time constant	1.71 ms
Thermal time constant	30 min
Shaft torsional stiffness	5,300 Nm/rad
Net weight of the motor	7.1 kg

Recommended Motor Module	
Rated inverter current	3 A
Maximum inverter current	9 A
Maximum torque	6.50 Nm

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	36
Cooling	Natural cooling
Radial runout tolerance	0.035 mm
Concentricity tolerance	0.08 mm
Axial runout tolerance	0.08 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP65
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	Standard (Anthracite RAL 7016)
Holding brake	without holding brake
Shaft end	Plain shaft
Encoder system	Encoder AM20DQI: absolute encoder 20 bits (resolution 1048576, encoder-internal 512 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)

Gearbox data	
Gearbox type	Planetary gearbox SP+
Designation	SP 075S-MF2
Gearbox shaft end	With feather key
Gear ratio + steps	28 (2-step)
Motor speed S3-60 %	8,500 rpm
Motor speed S1	3,500 rpm
Output torque S1	101 Nm
Rated output torque at duty type S3-60 %	126 Nm
Moment of inertia of gearbox	0.180 kgcm²
Radial output shaft loading, max.	4,200 N
Axial output shaft load, max.	3,350 N
Efficiency of gearbox	0.94
Torsional backlash	6 ′
Gearbox weight	3.60 kg

Limiting data	
Max. permissible speed (mech.)	10,000 rpm
Max. permissible speed (inverter)	10,000 rpm
Maximum torque	6.5 Nm
Maximum current	8.0 A

Check Price on Turll.com

Technical data are subject to change! There may be discrepancies.

Global Automation Distributor | TURLL.com

SIEMENS

Data sheet for SIMOTICS S-1FK7 servo geared motor



Figure similar

Article No. : 1FK7034-2AK71-1RG1-Z
J15

Special design

J15 Mounting of SP+ planetary gearbox

Check Price on Turll.com

Technical data are subject to change! There may be discrepanc

TURLL

YOUR GLOBAL AUTOMATION PARTNER

1FK7034-2AK71-1RG1-ZJ15

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

CHECK STOCK & PRICE

Need Assistance? Scan to Chat on WhatsApp

sales@turll.com | +852 6339 7344