



Data sheet for SIMOTICS S-1FK7 servo geared motor




Figure similar

Article No. : 1FK7040-2AK71-1RH1-Z
J29+X01

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data	
Rated speed (100 K)	6,000 rpm
Number of poles	8
Rated torque (100 K)	1.1 Nm
Rated current	1.9 A
Static torque (60 K)	1.30 Nm
Static torque (100 K)	1.60 Nm
Stall current (60 K)	1.90 A
Stall current (100 K)	2.35 A
Moment of inertia	2.460 kgcm²

Physical constants	
Torque constant	0.68 Nm/A
Voltage constant at 20° C	43.4 V/1000*min ⁻¹
Winding resistance at 20° C	2.87 Ω
Rotating field inductance	16.5 mH
Electrical time constant	5.70 ms
Mechanical time constant	3.00 ms
Thermal time constant	25 min
Shaft torsional stiffness	13,000 Nm/rad
Net weight of the motor	7.8 kg

Recommended Motor Module	
Rated inverter current	3 A
Maximum inverter current	9 A
Maximum torque	5.10 Nm

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	48
Cooling	Natural cooling
Radial runout tolerance	0.040 mm
Concentricity tolerance	0.08 mm
Axial runout tolerance	0.08 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP65
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	Jet black, matt RAL 9005
Holding brake	with holding brake
Shaft end	Plain shaft
Encoder system	Encoder AM20DQI: absolute encoder 20 bits (resolution 1048576, encoder-internal 512 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)

Gearbox data	
Gearbox type	Planetary gearbox SP+
Designation	SP 075S-MF1
Gearbox shaft end	Without feather key
Gear ratio + steps	10 (1-step)
Motor speed S3-60 %	7,500 rpm
Motor speed S1	3,100 rpm
Output torque S1	81 Nm
Rated output torque at duty type S3-60 %	114 Nm
Moment of inertia of gearbox	0.540 kgcm²
Radial output shaft loading, max.	4,200 N
Axial output shaft load, max.	3,350 N
Efficiency of gearbox	0.97
Torsional backlash	4 ´
Gearbox weight	3.90 kg

Limiting data	
Max. permissible speed (mech.)	9,000 rpm
Max. permissible speed (inverter)	9,000 rpm
Maximum torque	5.1 Nm
Maximum current	7.7 A



Data sheet for SIMOTICS S-1FK7 servo geared motor

Article No. : 1FK7040-2AK71-1RH1-Z
J29+X01



Figure similar

Holding brake	
Holding brake version	Permanent-magnet brake
Holding torque	4.0 Nm
Power supply voltage	DC 24 V ± 10 %
Coil current	0.5 A
Opening time	70 ms
Closing time	30 ms
Highest braking work	150 J

Special design	
J29	Mounting of SP+ planetary gearbox
X01	Paint finish: Jet black, matt RAL 9005

TURLL

YOUR GLOBAL AUTOMATION PARTNER

1FK7040-2AK71-1RH1-ZJ29X01

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

CHECK STOCK & PRICE



Need Assistance? Scan to Chat on WhatsApp

sales@turll.com | +852 6339 7344