

Data sheet for SIMOTICS S-1FK7

Article No. : 1FK7042-2AF21-1CB1



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

| | |
|-----------------------|-------------------------|
| Rated speed (100 K) | 3,000 rpm |
| Number of poles | 8 |
| Rated torque (100 K) | 2.6 Nm |
| Rated current | 3.5 A |
| Static torque (60 K) | 2.50 Nm |
| Static torque (100 K) | 3.00 Nm |
| Stall current (60 K) | 3.20 A |
| Stall current (100 K) | 3.95 A |
| Moment of inertia | 3.200 kgcm ² |
| Efficiency | 88.0 % |

Physical constants

| | |
|-----------------------------|-------------------------------|
| Torque constant | 0.76 Nm/A |
| Voltage constant at 20° C | 49.6 V/1000*min ⁻¹ |
| Winding resistance at 20° C | 1.44 Ω |
| Rotating field inductance | 10.6 mH |
| Electrical time constant | 7.40 ms |
| Mechanical time constant | 2.15 ms |
| Thermal time constant | 30 min |
| Shaft torsional stiffness | 11,400 Nm/rad |
| Net weight of the motor | 5.3 kg |

Mechanical data

| | |
|--------------------------|---|
| Motor type | Permanent-magnet synchronous motor |
| Motor type | Compact |
| Shaft height | 48 |
| Cooling | Natural cooling |
| Radial runout tolerance | 0.040 mm |
| Concentricity tolerance | 0.08 mm |
| Axial runout tolerance | 0.08 mm |
| Vibration severity grade | Grade A |
| Connector size | 1 |
| Degree of protection | IP65 |
| Design acc. to Code I | IM B5 (IM V1, IM V3) |
| Temperature monitoring | Pt1000 temperature sensor |
| Electrical connectors | Connectors for signals and power rotatable |
| Color of the housing | Standard (Anthracite RAL 7016) |
| Holding brake | with holding brake |
| Shaft end | Feather key |
| Encoder system | Encoder AM24DQI: absolute encoder 24 bits (resolution 16777216, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions) |

Optimum operating point

| | |
|---------------|-----------|
| Optimum speed | 3,000 rpm |
| Optimum power | 0.8 kW |

Limiting data

| | |
|-----------------------------------|-----------|
| Max. permissible speed (mech.) | 9,000 rpm |
| Max. permissible speed (inverter) | 5,800 rpm |
| Maximum torque | 10.5 Nm |
| Maximum current | 13.8 A |

Holding brake

| | |
|-----------------------|------------------------|
| Holding brake version | Permanent-magnet brake |
| Holding torque | 4.0 Nm |
| Power supply voltage | DC 24 V ± 10 % |
| Coil current | 0.5 A |
| Opening time | 70 ms |
| Closing time | 30 ms |
| Highest braking work | 150 J |

Recommended Motor Module

| | |
|--------------------------|---------|
| Rated inverter current | 4 A |
| Maximum inverter current | 8 A |
| Maximum torque | 6.00 Nm |

TURLL

YOUR GLOBAL AUTOMATION PARTNER

1FK7042-2AF21-1CB1

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

sales@turl.com | +852 6339 7344