

Data sheet for SIMOTICS S-1FK7 servo geared motor

Article No. : 1FK7042-2AF71-1CG1-Z
J17

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :



Figure similar

Engineering data

Rated speed (100 K)	3,000 rpm
Number of poles	8
Rated torque (100 K)	2.6 Nm
Rated current	2.0 A
Static torque (60 K)	2.50 Nm
Static torque (100 K)	3.00 Nm
Stall current (60 K)	1.80 A
Stall current (100 K)	2.20 A
Moment of inertia	3.440 kgcm ²

Physical constants

Torque constant	1.38 Nm/A
Voltage constant at 20° C	90.0 V/1000*min ⁻¹
Winding resistance at 20° C	4.67 Ω
Rotating field inductance	35.0 mH
Electrical time constant	7.50 ms
Mechanical time constant	2.15 ms
Thermal time constant	30 min
Shaft torsional stiffness	15,500 Nm/rad
Net weight of the motor	12.5 kg

Recommended Motor Module

Rated inverter current	3 A
Maximum inverter current	9 A
Maximum torque	10.50 Nm

Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	48
Cooling	Natural cooling
Radial runout tolerance	0.040 mm
Concentricity tolerance	0.08 mm
Axial runout tolerance	0.08 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP65
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	Standard (Anthracite RAL 7016)
Holding brake	without holding brake
Shaft end	Plain shaft
Encoder system	Encoder AM24DQI: absolute encoder 24 bits (resolution 16777216, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)

Gearbox data

Gearbox type	Planetary gearbox SP+
Designation	SP 100S-MF2
Gearbox shaft end	With feather key
Gear ratio + steps	50 (2-step)
Motor speed S3-60 %	6,500 rpm
Motor speed S1	3,500 rpm
Output torque S1	277 Nm
Rated output torque at duty type S3-60 %	347 Nm
Moment of inertia of gearbox	0.540 kgcm ²
Radial output shaft loading, max.	6,600 N
Axial output shaft load, max.	5,650 N
Efficiency of gearbox	0.94
Torsional backlash	5 '
Gearbox weight	7.90 kg

Limiting data

Max. permissible speed (mech.)	9,000 rpm
Max. permissible speed (inverter)	6,400 rpm
Maximum torque	10.5 Nm
Maximum current	7.6 A

Data sheet for SIMOTICS S-1FK7 servo geared motor

Article No. : 1FK7042-2AF71-1CG1-Z
J17



Figure similar

Special design

J17 Mounting of SP+ planetary gearbox

TURLL

YOUR GLOBAL AUTOMATION PARTNER

1FK7042-2AF71-1CG1-ZJ17

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

CHECK STOCK & PRICE



Need Assistance? Scan to Chat on WhatsApp

sales@turll.com | +852 6339 7344