

## Data sheet for SIMOTICS S-1FK7

Article No. : 1FK7042-2AF71-1PA0

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :



Figure similar

### Engineering data

|                       |                         |
|-----------------------|-------------------------|
| Rated speed (100 K)   | 3,000 rpm               |
| Number of poles       | 8                       |
| Rated torque (100 K)  | 2.6 Nm                  |
| Rated current         | 2.0 A                   |
| Static torque (60 K)  | 2.50 Nm                 |
| Static torque (100 K) | 3.00 Nm                 |
| Stall current (60 K)  | 1.80 A                  |
| Stall current (100 K) | 2.20 A                  |
| Moment of inertia     | 2.900 kgcm <sup>2</sup> |
| Efficiency            | 89.0 %                  |

### Physical constants

|                             |                               |
|-----------------------------|-------------------------------|
| Torque constant             | 1.38 Nm/A                     |
| Voltage constant at 20° C   | 90.0 V/1000*min <sup>-1</sup> |
| Winding resistance at 20° C | 4.67 Ω                        |
| Rotating field inductance   | 35.0 mH                       |
| Electrical time constant    | 7.50 ms                       |
| Mechanical time constant    | 2.15 ms                       |
| Thermal time constant       | 30 min                        |
| Shaft torsional stiffness   | 15,500 Nm/rad                 |
| Net weight of the motor     | 4.6 kg                        |

### Mechanical data

|                          |                                                                      |
|--------------------------|----------------------------------------------------------------------|
| Motor type               | Permanent-magnet synchronous motor                                   |
| Motor type               | Compact                                                              |
| Shaft height             | 48                                                                   |
| Cooling                  | Natural cooling                                                      |
| Radial runout tolerance  | 0.040 mm                                                             |
| Concentricity tolerance  | 0.08 mm                                                              |
| Axial runout tolerance   | 0.08 mm                                                              |
| Vibration severity grade | Grade A                                                              |
| Connector size           | 1                                                                    |
| Degree of protection     | IP64                                                                 |
| Design acc. to Code I    | IM B5 (IM V1, IM V3)                                                 |
| Temperature monitoring   | Pt1000 temperature sensor                                            |
| Electrical connectors    | Connectors for signals and power rotatable                           |
| Color of the housing     | Standard (Anthracite RAL 7016)                                       |
| Holding brake            | without holding brake                                                |
| Shaft end                | Feather key                                                          |
| Encoder system           | Resolver R14DQ: resolver 14 bits (resolution 16384, internal 2-pole) |

### Optimum operating point

|               |           |
|---------------|-----------|
| Optimum speed | 3,000 rpm |
| Optimum power | 0.8 kW    |

### Limiting data

|                                   |           |
|-----------------------------------|-----------|
| Max. permissible speed (mech.)    | 9,000 rpm |
| Max. permissible speed (inverter) | 6,400 rpm |
| Maximum torque                    | 10.5 Nm   |
| Maximum current                   | 7.6 A     |

### Recommended Motor Module

|                          |          |
|--------------------------|----------|
| Rated inverter current   | 3 A      |
| Maximum inverter current | 9 A      |
| Maximum torque           | 10.50 Nm |

# TURLL

YOUR GLOBAL AUTOMATION PARTNER

## 1FK7042-2AF71-1PA0

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

CHECK STOCK & PRICE



Need Assistance? Scan to Chat on WhatsApp

[sales@turll.com](mailto:sales@turll.com) | +852 6339 7344