

## Data sheet for SIMOTICS S-1FK7 servo geared motor



Figure similar

Article No. : **1FK7060-2AF71-1QG1-Z**  
J22

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

Rated speed (100 K)	3,000 rpm
Number of poles	8
Rated torque (100 K)	4.7 Nm
Rated current	3.7 A
Static torque (60 K)	5.00 Nm
Static torque (100 K)	6.00 Nm
Stall current (60 K)	3.60 A
Stall current (100 K)	4.45 A
Moment of inertia	10.740 kgcm <sup>2</sup>

### Physical constants

Torque constant	1.33 Nm/A
Voltage constant at 20° C	85.5 V/1000*min <sup>-1</sup>
Winding resistance at 20° C	1.35 Ω
Rotating field inductance	15.2 mH
Electrical time constant	11.30 ms
Mechanical time constant	1.71 ms
Thermal time constant	30 min
Shaft torsional stiffness	40,500 Nm/rad
Net weight of the motor	14.8 kg

### Recommended Motor Module

Rated inverter current	5 A
Maximum inverter current	15 A
Maximum torque	18.00 Nm

### Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	63
Cooling	Natural cooling
Radial runout tolerance	0.040 mm
Concentricity tolerance	0.10 mm
Axial runout tolerance	0.10 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP65
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	Standard (Anthracite RAL 7016)
Holding brake	without holding brake
Shaft end	Plain shaft
Encoder system	Encoder AS20DQI: absolute encoder single-turn 20 bits

### Gearbox data

Gearbox type	Planetary gearbox SP+
Designation	SP 100S-MF1
Gearbox shaft end	Without feather key
Gear ratio + steps	4 (1-step)
Motor speed S3-60 %	5,500 rpm
Motor speed S1	2,500 rpm
Output torque S1	171 Nm
Rated output torque at duty type S3-60 %	378 Nm
Moment of inertia of gearbox	3.040 kgcm <sup>2</sup>
Radial output shaft loading, max.	6,600 N
Axial output shaft load, max.	5,650 N
Efficiency of gearbox	0.97
Torsional backlash	3 '
Gearbox weight	7.70 kg

### Limiting data

Max. permissible speed (mech.)	7,200 rpm
Max. permissible speed (inverter)	6,700 rpm
Maximum torque	18.0 Nm
Maximum current	15.0 A

### Special design

J22 — Mounting of SP+ planetary gearbox

# SIEMENS

## Data sheet for SIMOTICS S-1FK7 servo geared motor

Article No. : **1FK7060-2AF71-1QG1-Z**  
J22



Figure similar

# TURLL

YOUR GLOBAL AUTOMATION PARTNER

## 1FK7060-2AF71-1QG1-ZJ22

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

[sales@turl.com](mailto:sales@turl.com) | +852 6339 7344