

Data sheet for SIMOTICS S-1FK7

Article No. : 1FK7060-2AH71-1FH0



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

Rated speed (100 K)	4,500 rpm
Number of poles	8
Rated torque (100 K)	3.7 Nm
Rated current	4.3 A
Static torque (60 K)	5.00 Nm
Static torque (100 K)	6.00 Nm
Stall current (60 K)	5.10 A
Stall current (100 K)	6.30 A
Moment of inertia	8.700 kgcm ²
Efficiency	90.0 %

Physical constants

Torque constant	0.95 Nm/A
Voltage constant at 20° C	60.5 V/1000*min ⁻¹
Winding resistance at 20° C	0.69 Ω
Rotating field inductance	7.6 mH
Electrical time constant	10.90 ms
Mechanical time constant	1.78 ms
Thermal time constant	30 min
Shaft torsional stiffness	28,500 Nm/rad
Net weight of the motor	8.5 kg

Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	63
Cooling	Natural cooling
Radial runout tolerance	0.040 mm
Concentricity tolerance	0.10 mm
Axial runout tolerance	0.10 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP64
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	Standard (Anthracite RAL 7016)
Holding brake	with holding brake
Shaft end	Plain shaft
Encoder system	Encoder AM22DQ: absolute encoder 22 bits (resolution 4194304, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)

Optimum operating point

Optimum speed	4,500 rpm
Optimum power	1.7 kW

Limiting data

Max. permissible speed (mech.)	7,200 rpm
Max. permissible speed (inverter)	7,200 rpm
Maximum torque	18.0 Nm
Maximum current	21.5 A

Holding brake

Holding brake version	Permanent-magnet brake
Holding torque	13.0 Nm
Power supply voltage	DC 24 V ± 10 %
Coil current	0.8 A
Opening time	100 ms
Closing time	50 ms
Highest braking work	380 J

Recommended Motor Module

Rated inverter current	9 A
Maximum inverter current	27 A
Maximum torque	18.00 Nm

TURLL

YOUR GLOBAL AUTOMATION PARTNER

1FK7060-2AH71-1FH0

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

sales@turl.com | +852 6339 7344