

# SIEMENS

## Data sheet

**5SE2325**


NEOZED fuse-link, D02, 25 A, gG, Un AC: 400 V, Un DC: 250 V, with tin-coated contact-caps

Figure similar

Model	
product brand name	SENTRON
product designation	NEOZED fuse link
design of the product	With tin-coated contact caps
product version	Pack of 10
design of the fuse link	NEOZED fuse link
General technical data	
size of fuse system according to EN 60269-1	D02
operating class of the fuse link	gG
Supply voltage	
supply voltage	
• at AC	400 V
• at DC	250 V
operating voltage rated value	400 V
protection class IP	IP20, with connected conductors
switching capacity current according to IEC 60947-2 rated value	50 kA
Dissipation	
power loss [W] for rated value of the current at AC in hot operating state per pole	1.7 W
Main circuit	
operational current rated value	25 A
Appearance	
color coding of the fuse link	Yellow
maximum short-circuit current breaking capacity (I <sub>cu</sub> ) at AC rated value	50 kA
Mechanical Design	
mounting position	Any, preferably vertical
Net Weight	13 g
ambient temperature during operation	
• minimum	-25 °C
• maximum	40 °C
environmental category	Up to 45°C at 95 % rel. humidity
Approvals Certificates	
General Product Approval	



Confirmation



other

Environment



Confirmation

Environmental Con-  
firmationsEnvironmental Con-  
firmations

## Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SE2325>

Service&amp;Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SE2325>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SE2325](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SE2325)


CAx-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP='HAUPT'></mmp_prod_no>)

last modified:

4/10/2025



# TURLL

YOUR GLOBAL AUTOMATION PARTNER

## 5SE2325

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

[sales@turl.com](mailto:sales@turl.com) | +852 6339 7344