

Siemens
EcoTech



SIMATIC ET 200SP HA, digital input module, DI 16x24VDC HA, suitable for terminal block H1, M1, color code CC01, channel diagnostics

General information	
Product type designation	DI 16x24VDC HA
Firmware version	V1.0
<ul style="list-style-type: none"> FW update possible 	Yes
Usable terminal block	type H1, M1, N0, H0, M0 (for details see the system manual)
Color code for module-specific color-coded label	CC01
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 to I&M3
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version 	V16
<ul style="list-style-type: none"> STEP 7 configurable/integrated from version 	V5.6
<ul style="list-style-type: none"> PCS 7 configurable/integrated from version 	V9.0
<ul style="list-style-type: none"> PCS neo can be configured/integrated from version 	V3.0
<ul style="list-style-type: none"> PROFINET from GSD version/GSD revision 	GSDML V2.3
Operating mode	
<ul style="list-style-type: none"> DI 	Yes
<ul style="list-style-type: none"> Counter 	No
<ul style="list-style-type: none"> Oversampling 	No
<ul style="list-style-type: none"> MSI 	No
Redundancy	
<ul style="list-style-type: none"> Redundancy capability 	Yes; With TB type M1
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption (rated value)	60 mA; without sensor supply
Current consumption, max.	120 mA; without sensor supply
Encoder supply	
Number of outputs	16
Output voltage, min.	18.2 V; L+ (-1 V)
Short-circuit protection	Yes; electronic (response threshold 0.7 A to 1.3 A; for IO redundancy up to 2.6 A) Ensure sufficient low-resistance cable routing to the sensor/actuator in order to attain the response threshold. Depending on the cable cross-section used, there may be constraints regarding the usable length of cable
Output current	

<ul style="list-style-type: none"> • up to 60 °C, max. 	2 A; 1 A when mounted vertically; see derating information in Equipment Manual
<ul style="list-style-type: none"> • up to 70 °C, max. 	1 A; See derating information in Equipment Manual
24 V encoder supply	
<ul style="list-style-type: none"> • 24 V 	Yes
<ul style="list-style-type: none"> • Short-circuit protection 	Yes; electronic (response threshold 0.7 A to 1.3 A; for IO redundancy up to 2.6 A) Ensure sufficient low-resistance cable routing to the sensor/actuator in order to attain the response threshold. Depending on the cable cross-section used, there may be constraints regarding the usable length of cable
<ul style="list-style-type: none"> • Output current per channel, max. 	0.5 A
<ul style="list-style-type: none"> • Output current per module, max. 	2 A
Power	
Power consumption from the backplane bus	80 mW
Power loss	
Power loss, typ.	3.6 W; Maximum value (taking the max. encoder current and the max. operating voltage into account)
Address area	
Address space per module	
<ul style="list-style-type: none"> • Address space per module, max. 	2 byte; + 2 bytes for QI information (additional 18 bytes when using high-precision time stamping)
Hardware configuration	
Automatic encoding	
<ul style="list-style-type: none"> • Mechanical coding element 	Yes
Digital inputs	
Number of digital inputs	16
Digital inputs, parameterizable	Yes
Sourcing/sinking input	Yes; P-reading
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Input characteristic curve in accordance with IEC 61131, type 2	No
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Pulse extension	Yes
<ul style="list-style-type: none"> • Length 	off, 50 ms, 100 ms, 200 ms, 500 ms, 1 s, 2 s
Time stamp (with precision of 1 ms)	Yes; Resolution 1ms
Edge evaluation	Yes; rising edge, falling edge, edge change
Input voltage	
<ul style="list-style-type: none"> • Rated value (DC) 	24 V
<ul style="list-style-type: none"> • for signal "0" 	-30 to +5 V
<ul style="list-style-type: none"> • for signal "1" 	+11 to +30V
Input current	
<ul style="list-style-type: none"> • for signal "1", typ. 	2.5 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; none / 0.05 / 0.1 / 0.4 / 0.8 / 1.6 / 3.2 / 12.8 / 20 ms
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	1 000 m
<ul style="list-style-type: none"> • unshielded, max. 	600 m
Encoder	
Connectable encoders	
<ul style="list-style-type: none"> • 2-wire sensor 	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
<ul style="list-style-type: none"> • Diagnostic alarm 	Yes; channel by channel
<ul style="list-style-type: none"> • Hardware interrupt 	Yes; channel by channel
Diagnoses	
<ul style="list-style-type: none"> • Diagnostic information readable 	Yes
<ul style="list-style-type: none"> • Monitoring the supply voltage 	Yes; module-wise
— parameterizable	Yes
<ul style="list-style-type: none"> • Monitoring of encoder power supply 	Yes

<ul style="list-style-type: none"> • Wire break 	Yes; Channel-by-channel, optional protective circuit for preventing wire-break diagnostics in the case of simple encoder contacts: 15 kOhm to 18 kOhm
<ul style="list-style-type: none"> • Short-circuit to ground 	Yes; Encoder supply to M, channel by channel
Diagnostics indication LED	
<ul style="list-style-type: none"> • MAINT LED 	Yes; Yellow LED
<ul style="list-style-type: none"> • Monitoring of the supply voltage (PWR-LED) 	Yes; green PWR LED
<ul style="list-style-type: none"> • Channel status display 	Yes; green LED
<ul style="list-style-type: none"> • for channel diagnostics 	Yes; red LED
<ul style="list-style-type: none"> • for module diagnostics 	Yes; green/red LED
Potential separation	
Potential separation channels	
<ul style="list-style-type: none"> • between the channels 	No
<ul style="list-style-type: none"> • between the channels and backplane bus 	Yes
<ul style="list-style-type: none"> • between the channels and the power supply of the electronics 	No
Isolation	
Isolation tested with	1 500 V DC/1 min, type test
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> • horizontal installation, min. 	-40 °C
<ul style="list-style-type: none"> • horizontal installation, max. 	70 °C
<ul style="list-style-type: none"> • vertical installation, min. 	-40 °C
<ul style="list-style-type: none"> • vertical installation, max. 	60 °C
Dimensions	
Width	22.5 mm
Height	115 mm
Depth	138 mm
Weights	
Weight, approx.	135 g
Classifications	

	Version	Classification
eClass	14	27-24-26-04
eClass	12	27-24-26-04
eClass	9.1	27-24-26-04
eClass	9	27-24-26-04
eClass	8	27-24-26-04
eClass	7.1	27-24-26-04
eClass	6	27-24-26-04
ETIM	10	EC001599
ETIM	9	EC001599
ETIM	8	EC001599
ETIM	7	EC001599

Approvals / Certificates

General Product Approval



EG-Konf.

[Miscellaneous](#)




[Declaration of Conformity](#)





RCM

General Product Approval For use in hazardous locations





IECEX

[Declaration of Conformity](#)



CCC



UL



ATEX

For use in hazardous locations	Maritime application
--------------------------------	----------------------



IECEX

[Miscellaneous](#)



ABS



BUREAU
VERITAS



DNV



LRS

Maritime application	Environment
----------------------	-------------

[NK / Nippon Kaiji Ky-
okai](#)



RINA

[CCS \(China Classifica-
tion Society\)](#)

Siemens
EcoTech



last modified:

3/10/2026

TURLL

YOUR GLOBAL AUTOMATION PARTNER

6DL1131-6BH00-0PH1

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

sales@turl.com | +852 6339 7344