

## Data sheet

## 6ED1057-4CA00-0AA0



LOGO! contact 24 Switching module for direct switching of resistive loads up to 20 A and motors up to 4 kW, 24 V DC, 3 NO contacts+1 NC EAN: 4025515050742

Supply voltage		
Rated value (DC)		
• 24 V DC	Yes	
Standards, approvals, certificates		
CE mark	Yes	
Ambient conditions		
Ambient temperature during operation		
• min.	-25 °C	
• max.	55 °C	
Dimensions		
Width	36 mm	
Height	72 mm	
Depth	55 mm	
Weights		
Weight, approx.	160 g	
Classifications		
	<b>Version</b>	<b>Classification</b>
eClass	14	27-24-22-16
eClass	12	27-24-22-16
eClass	9.1	27-24-22-16
eClass	9	27-24-22-16
eClass	8	27-24-22-16
eClass	7.1	27-24-22-16
eClass	6	27-24-22-16
ETIM	10	EC001417
ETIM	9	EC001417
ETIM	8	EC001417
ETIM	7	EC001417
IDEA	4	3565
UNSPSC	15	32-15-17-05
Approvals / Certificates		
General Product Approval	Maritime application	


[Manufacturer Declaration](#)

[KC](#)



---

last modified:

5/22/2024 

# TURLL

YOUR GLOBAL AUTOMATION PARTNER

## 6ED1057-4CA00-0AA0

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

[sales@turl.com](mailto:sales@turl.com) | +852 6339 7344