



SIMATIC ET 200SP, digital output module, DQ 4x 24...230V AC/2A Standard suitable for BU type B1, Color code CC41, Module diagnostics

General information	
Product type designation	DQ 4x24 ... 230 V AC/2 A ST
HW functional status	From FS05
Firmware version	V1.0
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
usable BaseUnits	BU type B1
Color code for module-specific color identification plate	CC41
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> <li>Isochronous mode</li> </ul>	No
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul>	V13 / V13
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated from version</li> </ul>	V5.5 SP3 / -
<ul style="list-style-type: none"> <li>PROFIBUS from GSD version/GSD revision</li> </ul>	GSD Revision 5
<ul style="list-style-type: none"> <li>PROFINET from GSD version/GSD revision</li> </ul>	GSDML V2.3
Operating mode	
<ul style="list-style-type: none"> <li>DQ</li> </ul>	Yes
<ul style="list-style-type: none"> <li>DQ with energy-saving function</li> </ul>	No
<ul style="list-style-type: none"> <li>PWM</li> </ul>	No
<ul style="list-style-type: none"> <li>Oversampling</li> </ul>	No
<ul style="list-style-type: none"> <li>MSO</li> </ul>	No
Supply voltage	
Rated value (AC)	230 V
permissible range, lower limit (AC)	20.4 V
permissible range, upper limit (AC)	264 V
Input current	
Current consumption (rated value)	11.5 mA
Output voltage	
Rated value (AC)	230 V; 24V AC to 230V AC
Power loss	
Power loss, typ.	9 W; Active power, load voltage 230 V, all outputs loaded with 2 A, 50 Hz
Address area	
Address space per module	
<ul style="list-style-type: none"> <li>Address space per module, max.</li> </ul>	1 byte; + 1 byte for QI information
<ul style="list-style-type: none"> <li>Inputs</li> </ul>	1 byte; With QI
<ul style="list-style-type: none"> <li>Outputs</li> </ul>	1 byte

Hardware configuration	
Automatic encoding	
<ul style="list-style-type: none"> <li>Type of mechanical coding element</li> </ul>	type C
Digital outputs	
Type of digital output	Triac with zero point detection
Number of digital outputs	4
Current-sinking	No
Current-sourcing	Yes
Digital outputs, parameterizable	No
Short-circuit protection	No; When using BU type B1, a miniature, quick-response fuse with 10 A tripping current must be provided
Controlling a digital input	Yes
Size of motor starters according to NEMA, max.	5
Switching capacity of the outputs	
<ul style="list-style-type: none"> <li>with resistive load, max.</li> </ul>	2 A
<ul style="list-style-type: none"> <li>on lamp load, max.</li> </ul>	100 W
Output voltage	
<ul style="list-style-type: none"> <li>for signal "1", min.</li> </ul>	20.4 V
Output current	
<ul style="list-style-type: none"> <li>for signal "1" rated value</li> </ul>	2 A
<ul style="list-style-type: none"> <li>for signal "1" permissible range, min.</li> </ul>	10 mA
<ul style="list-style-type: none"> <li>for signal "1" permissible range, max.</li> </ul>	2 A
<ul style="list-style-type: none"> <li>for signal "0" residual current, max.</li> </ul>	460 $\mu$ A
Output delay with resistive load	
<ul style="list-style-type: none"> <li>"0" to "1", max.</li> </ul>	10 ms
<ul style="list-style-type: none"> <li>"1" to "0", max.</li> </ul>	10 ms
Parallel switching of two outputs	
<ul style="list-style-type: none"> <li>for logic links</li> </ul>	No
<ul style="list-style-type: none"> <li>for uprating</li> </ul>	No
<ul style="list-style-type: none"> <li>for redundant control of a load</li> </ul>	Yes
Switching frequency	
<ul style="list-style-type: none"> <li>with resistive load, max.</li> </ul>	10 Hz
<ul style="list-style-type: none"> <li>with inductive load, max.</li> </ul>	0.5 Hz; Higher frequencies are possible, see Equipment Manual / Product Information
<ul style="list-style-type: none"> <li>on lamp load, max.</li> </ul>	1 Hz
Total current of the outputs	
<ul style="list-style-type: none"> <li>Current per channel, max.</li> </ul>	2 A
<ul style="list-style-type: none"> <li>Current per module, max.</li> </ul>	8 A
Total current of the outputs (per module)	
horizontal installation	
<ul style="list-style-type: none"> <li>— up to 40 °C, max.</li> </ul>	8 A
<ul style="list-style-type: none"> <li>— up to 50 °C, max.</li> </ul>	6 A
<ul style="list-style-type: none"> <li>— up to 60 °C, max.</li> </ul>	4 A
vertical installation	
<ul style="list-style-type: none"> <li>— up to 30 °C, max.</li> </ul>	8 A
<ul style="list-style-type: none"> <li>— up to 40 °C, max.</li> </ul>	6 A
<ul style="list-style-type: none"> <li>— up to 50 °C, max.</li> </ul>	4 A
Cable length	
<ul style="list-style-type: none"> <li>shielded, max.</li> </ul>	1 000 m
<ul style="list-style-type: none"> <li>unshielded, max.</li> </ul>	600 m
Interrupts/diagnostics/status information	
Diagnostics function	No
Substitute values connectable	Yes
Alarms	
<ul style="list-style-type: none"> <li>Diagnostic alarm</li> </ul>	No
Diagnoses	
<ul style="list-style-type: none"> <li>Monitoring the supply voltage</li> </ul>	No
<ul style="list-style-type: none"> <li>Wire-break</li> </ul>	No
<ul style="list-style-type: none"> <li>Short-circuit</li> </ul>	No

• Group error	Yes	
<b>Diagnostics indication LED</b>		
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED	
• Channel status display	Yes; green LED	
• for channel diagnostics	No	
• for module diagnostics	Yes; green/red DIAG LED	
<b>Potential separation</b>		
<b>Potential separation channels</b>		
• between the channels	No	
• between the channels and backplane bus	Yes	
• between the channels and the power supply of the electronics	No	
<b>Isolation</b>		
Isolation tested with	2 545 V DC/2 s (routine test)	
<b>Standards, approvals, certificates</b>		
Suitable for safety functions	No	
<b>Ecological footprint</b>		
• environmental product declaration	Yes	
<b>Global warming potential</b>		
— global warming potential, (total) [CO2 eq]	13.9 kg	
— global warming potential, (during production) [CO2 eq]	5.53 kg	
— global warming potential, (during operation) [CO2 eq]	8.71 kg	
— global warming potential, (after end of life cycle) [CO2 eq]	-0.359 kg	
<b>Ambient conditions</b>		
<b>Ambient temperature during operation</b>		
• horizontal installation, min.	-30 °C	
• horizontal installation, max.	60 °C	
• vertical installation, min.	-30 °C	
• vertical installation, max.	60 °C	
<b>Altitude during operation relating to sea level</b>		
• Installation altitude above sea level, max.	2 000 m; On request: Installation altitudes greater than 2 000 m	
<b>Dimensions</b>		
Width	20 mm	
Height	73 mm	
Depth	58 mm	
<b>Weights</b>		
Weight, approx.	50 g	
<b>Classifications</b>		
	<b>Version</b>	<b>Classification</b>
eClass	14	27-24-26-04
eClass	12	27-24-26-04
eClass	9.1	27-24-26-04
eClass	9	27-24-26-04
eClass	8	27-24-26-04
eClass	7.1	27-24-26-04
eClass	6	27-24-26-04
ETIM	10	EC001599
ETIM	9	EC001599
ETIM	8	EC001599
ETIM	7	EC001599
IDEA	4	3566
UNSPSC	15	32-15-17-05
<b>Approvals / Certificates</b>		
<b>General Product Approval</b>		



[Manufacturer Declaration](#)

[Miscellaneous](#)

[China RoHS](#)



General Product Approval

For use in hazardous locations

Maritime application

[KC](#)



[EM](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

Maritime application

Environment



Siemens EcoTech



last modified:

9/19/2025

# TURLL

YOUR GLOBAL AUTOMATION PARTNER

## 6ES7132-6FD00-0BB1

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

sales@turl.com | +852 6339 7344