



SIMATIC ET 200SP, Analog input module, AI 8xRTD/TC 2-wire High Feature suitable for BU type A0, A1, Color code CC00, channel diagnostics, 16 bit, +/-0.1%

General information	
Product type designation	AI 8xRTD/TC 2-wire HF
HW functional status	From FS05
Firmware version	V2.1
• FW update possible	Yes
usable BaseUnits	BU type A0, A1
Color code for module-specific color identification plate	CC00
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	No
• Measuring range scalable	Yes
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	V16, V17 / V18
• STEP 7 configurable/integrated from version	V5.5 SP3 / V5.5 SP4
• PCS 7 configurable/integrated from version	V8.1 SP1
• PROFIBUS from GSD version/GSD revision	One GSD file each, Revision 3 and 5 and higher
• PROFINET from GSD version/GSD revision	GSDML V2.35
Operating mode	
• Oversampling	No
• MSI	No
CIR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Calibration possible in RUN	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption, max.	35 mA
Power loss	
Power loss, typ.	0.75 W
Address area	
Address space per module	
• Address space per module, max.	16 byte; + 1 byte for QI information
Hardware configuration	

Automatic encoding	
<ul style="list-style-type: none"> • Mechanical coding element 	Yes
<ul style="list-style-type: none"> • Type of mechanical coding element 	Type A
Selection of BaseUnit for connection variants	
<ul style="list-style-type: none"> • 2-wire connection 	BU type A0, A1
Analog inputs	
Number of analog inputs	8
permissible input voltage for voltage input (destruction limit), max.	30 V
Constant measurement current for resistance-type transmitter, typ.	2 mA
Cycle time (all channels), min.	Sum of the basic conversion times and additional processing times (depending on the parameterization of the active channels)
Technical unit for temperature measurement adjustable	Yes; °C/°F/K
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> • -1 V to +1 V <ul style="list-style-type: none"> — Input resistance (-1 V to +1 V) 	Yes; 16 bit incl. sign 1 MΩ
<ul style="list-style-type: none"> • -250 mV to +250 mV <ul style="list-style-type: none"> — Input resistance (-250 mV to +250 mV) 	Yes; 16 bit incl. sign 1 MΩ
<ul style="list-style-type: none"> • -50 mV to +50 mV <ul style="list-style-type: none"> — Input resistance (-50 mV to +50 mV) 	Yes; 16 bit incl. sign 1 MΩ
<ul style="list-style-type: none"> • -80 mV to +80 mV <ul style="list-style-type: none"> — Input resistance (-80 mV to +80 mV) 	Yes; 16 bit incl. sign 1 MΩ
Input ranges (rated values), thermocouples	
<ul style="list-style-type: none"> • Type B <ul style="list-style-type: none"> — Input resistance (Type B) 	Yes; 16 bit incl. sign 1 MΩ
<ul style="list-style-type: none"> • Type C <ul style="list-style-type: none"> — Input resistance (Type C) 	Yes; 16 bit incl. sign 1 MΩ
<ul style="list-style-type: none"> • Type E <ul style="list-style-type: none"> — Input resistance (Type E) 	Yes; 16 bit incl. sign 1 MΩ
<ul style="list-style-type: none"> • Type J <ul style="list-style-type: none"> — Input resistance (type J) 	Yes; 16 bit incl. sign 1 MΩ
<ul style="list-style-type: none"> • Type K <ul style="list-style-type: none"> — Input resistance (Type K) 	Yes; 16 bit incl. sign 1 MΩ
<ul style="list-style-type: none"> • Type L <ul style="list-style-type: none"> — Input resistance (Type L) 	Yes; 16 bit incl. sign 1 MΩ
<ul style="list-style-type: none"> • Type N <ul style="list-style-type: none"> — Input resistance (Type N) 	Yes; 16 bit incl. sign 1 MΩ
<ul style="list-style-type: none"> • Type R <ul style="list-style-type: none"> — Input resistance (Type R) 	Yes; 16 bit incl. sign 1 MΩ
<ul style="list-style-type: none"> • Type S <ul style="list-style-type: none"> — Input resistance (Type S) 	Yes; 16 bit incl. sign 1 MΩ
<ul style="list-style-type: none"> • Type T <ul style="list-style-type: none"> — Input resistance (Type T) 	Yes; 16 bit incl. sign 1 MΩ
<ul style="list-style-type: none"> • Type U <ul style="list-style-type: none"> — Input resistance (Type U) 	Yes; 16 bit incl. sign 1 MΩ
<ul style="list-style-type: none"> • Type TXK/TXK(L) to GOST <ul style="list-style-type: none"> — Input resistance (Type TXK/TXK(L) to GOST) 	Yes; 16 bit incl. sign 1 MΩ
Input ranges (rated values), resistance thermometer	
<ul style="list-style-type: none"> • Ni 100 <ul style="list-style-type: none"> — Input resistance (Ni 100) 	Yes; 16 bit incl. sign 1 MΩ
<ul style="list-style-type: none"> • Ni 1000 <ul style="list-style-type: none"> — Input resistance (Ni 1000) 	Yes; 16 bit incl. sign 1 MΩ
<ul style="list-style-type: none"> • LG-Ni 1000 <ul style="list-style-type: none"> — Input resistance (LG-Ni 1000) 	Yes; 16 bit incl. sign 1 MΩ
<ul style="list-style-type: none"> • Ni 120 <ul style="list-style-type: none"> — Input resistance (Ni 120) 	Yes; 16 bit incl. sign 1 MΩ
<ul style="list-style-type: none"> • Ni 200 <ul style="list-style-type: none"> — Input resistance (Ni 200) 	Yes; 16 bit incl. sign 1 MΩ
<ul style="list-style-type: none"> • Ni 500 	Yes; 16 bit incl. sign

— Input resistance (Ni 500)	1 M Ω
• Pt 100	Yes; 16 bit incl. sign
— Input resistance (Pt 100)	1 M Ω
• Pt 1000	Yes; 16 bit incl. sign
— Input resistance (Pt 1000)	1 M Ω
• Pt 200	Yes; 16 bit incl. sign
— Input resistance (Pt 200)	1 M Ω
• Pt 500	Yes; 16 bit incl. sign
— Input resistance (Pt 500)	1 M Ω
Input ranges (rated values), resistors	
• 0 to 150 ohms	Yes; 15 bit
— Input resistance (0 to 150 ohms)	1 M Ω
• 0 to 300 ohms	Yes; 15 bit
— Input resistance (0 to 300 ohms)	1 M Ω
• 0 to 600 ohms	Yes; 15 bit
— Input resistance (0 to 600 ohms)	1 M Ω
• 0 to 3000 ohms	Yes; 15 bit
— Input resistance (0 to 3000 ohms)	1 M Ω
• 0 to 6000 ohms	Yes; 15 bit
— Input resistance (0 to 6000 ohms)	1 M Ω
• PTC	Yes; 15 bit
— Input resistance (PTC)	1 M Ω
Thermocouple (TC)	
Temperature compensation	
— parameterizable	Yes
— Reference channel of the module	Yes
— internal comparison point	Yes; with BaseUnit type A1
— Reference channel of the group	Yes
— Number of reference channel groups	4; Group 0 to 3
— fixed reference temperature	Yes
Cable length	
• shielded, max.	200 m; 50 m with thermocouples
Analog value generation for the inputs	
Measurement principle	integrating (Sigma-Delta)
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit
• Integration time, parameterizable	Yes
• Basic conversion time, including integration time (ms)	
— additional processing time for wire-break check	2 ms; In the ranges resistance thermometers, resistors and thermocouples
• Interference voltage suppression for interference frequency f1 in Hz	16.6 / 50 / 60 Hz
• Conversion time (per channel)	180 / 60 / 50 / (67.5 / 22.5 / 18.75) ms
Smoothing of measured values	
• Number of smoothing levels	4; None; 4/8/16 times
• parameterizable	Yes
Encoder	
Connection of signal encoders	
• for voltage measurement	Yes
• for resistance measurement with two-wire connection	Yes
• for resistance measurement with three-wire connection	No
• for resistance measurement with four-wire connection	No
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.01 %; ± 0.1 % for resistance thermometers and resistance
Temperature error (relative to input range), (+/-)	0.0009 %/K; ± 0.005 % / K at thermocouple
Crosstalk between the inputs, min.	-50 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.05 %
Operational error limit in overall temperature range	
• Voltage, relative to input range, (+/-)	0.1 %

• Resistance, relative to input range, (+/-)	0.1 %	
Basic error limit (operational limit at 25 °C)		
• Voltage, relative to input range, (+/-)	0.05 %	
• Resistance, relative to input range, (+/-)	0.05 %	
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, $f_1 =$ interference frequency		
• Series mode interference (peak value of interference < rated value of input range), min.	70 dB; With conversion time 67.5 / 22.5 / 18.75 ms: 40 dB	
• Common mode voltage, max.	10 V	
• Common mode interference, min.	90 dB	
Interrupts/diagnostics/status information		
Alarms		
• Diagnostic alarm	Yes	
• Limit value alarm	Yes; two upper and two lower limit values in each case	
Diagnoses		
• Monitoring the supply voltage	Yes	
• Wire-break	Yes; channel by channel	
• Group error	Yes	
• Overflow/underflow	Yes; channel by channel	
Diagnostics indication LED		
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED	
• Channel status display	Yes; green LED	
• for channel diagnostics	Yes; red LED	
• for module diagnostics	Yes; green/red DIAG LED	
Potential separation		
Potential separation channels		
• between the channels	No	
• between the channels and backplane bus	Yes	
• between the channels and the power supply of the electronics	Yes	
Permissible potential difference		
between the inputs (UCM)	10 V DC	
Isolation		
Isolation tested with	707 V DC (type test)	
Standards, approvals, certificates		
Ecological footprint		
• environmental product declaration	Yes	
Global warming potential		
— global warming potential, (total) [CO2 eq]	9.32 kg	
— global warming potential, (during production) [CO2 eq]	4.97 kg	
— global warming potential, (during operation) [CO2 eq]	4.79 kg	
— global warming potential, (after end of life cycle) [CO2 eq]	-0.449 kg	
Ambient conditions		
Ambient temperature during operation		
• horizontal installation, min.	-30 °C	
• horizontal installation, max.	60 °C	
• vertical installation, min.	-30 °C	
• vertical installation, max.	50 °C	
Altitude during operation relating to sea level		
• Installation altitude above sea level, max.	2 000 m; On request: Installation altitudes greater than 2 000 m	
Dimensions		
Width	15 mm	
Height	73 mm	
Depth	58 mm	
Classifications		
	Version	Classification
eClass	14	27-24-26-01

eClass	12	27-24-26-01
eClass	9.1	27-24-26-01
eClass	9	27-24-26-01
eClass	8	27-24-26-01
eClass	7.1	27-24-26-01
eClass	6	27-24-26-01
ETIM	10	EC001596
ETIM	9	EC001596
ETIM	8	EC001596
ETIM	7	EC001596
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval



[Miscellaneous](#)

[Manufacturer Declaration](#)

[China RoHS](#)



General Product Approval

For use in hazardous locations

[Metrological Approval](#)

[KC](#)



[EM](#)

[CCC-Ex](#)

For use in hazardous locations

Maritime application



[Type Examination Certificate](#)



[Miscellaneous](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

Maritime application

Environment



Siemens EcoTech



last modified:

10/23/2025

TURLL

YOUR GLOBAL AUTOMATION PARTNER

6ES7134-6JF00-0CA1

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

sales@turl.com | +852 6339 7344