

Data sheet

6ES7135-4GB01-0AB0



*** Spare part *** SIMATIC DP, Electronics module for ET 200S, 2 AO I 15 mm width, +/-20mA; 13 bit+sign, 4..20mA; 13 bit Cycle time less than 1 ms with SF LED (group fault)

General information	
Product function	
• Isochronous mode	No
Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V; From power module
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	150 mA
from backplane bus 3.3 V DC, max.	10 mA
Power loss	
Power loss, max.	2 W
Address area	
Address space per module	
• Address space per module, max.	4 byte
Analog outputs	
Number of analog outputs	2
Current output, no-load voltage, max.	18 V
Cycle time (all channels) max.	1.5 ms
Output ranges, current	
• -20 mA to +20 mA	Yes
• 4 mA to 20 mA	Yes
Connection of actuators	
• for current output two-wire connection	Yes
• for current output four-wire connection	No
Load impedance (in rated range of output)	
• with current outputs, max.	500 Ω
• with current outputs, inductive load, max.	1 mH
Destruction limits against externally applied voltages and currents	
• Voltages at the outputs towards MANA	15 V; max. 15 V continuous; 75 V for max. 1 s (mark to space ratio 1:20)
• Current, max.	50 mA; DC
Cable length	
• shielded, max.	200 m
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	14 bit; 4 to 20 mA: 13 bit, ±20 mA: 14 bit
Settling time	
• for resistive load	0.1 ms
• for capacitive load	0.5 ms

• for inductive load	0.5 ms
Errors/accuracies	
Operational error limit in overall temperature range	
• Current, relative to output range, (+/-)	0.5 %
Basic error limit (operational limit at 25 °C)	
• Current, relative to output range, (+/-)	0.3 %
Interrupts/diagnostics/status information	
Substitute values connectable	Yes; 0 to 65535 (range of values must be within the rated range)
Diagnoses	
• Diagnostic information readable	Yes
• Wire-break	Yes
• Group error	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
Parameter	
Remark	7 byte
Diagnostics wire break	Disable / enable
Group diagnostics	Disable / enable
Response to CPU/master STOP	Output current and de-energized/substitute a value/keep last value
Potential separation	
Potential separation analog outputs	
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes
Isolation	
Isolation tested with	500 V DC
Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm
Weights	
Weight, approx.	40 g
Classifications	

	Version	Classification
eClass	14	27-24-26-01
eClass	12	27-24-26-01
eClass	9.1	27-24-26-01
eClass	9	27-24-26-01
eClass	8	27-24-26-01
eClass	7.1	27-24-26-01
eClass	6	27-24-26-01
ETIM	10	EC001596
ETIM	9	EC001596
ETIM	8	EC001596
ETIM	7	EC001596
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates	
General Product Approval	

[Manufacturer Declaration](#)



[Miscellaneous](#)

[China RoHS](#)



General Product Ap-	EMV	For use in hazardous locations
---------------------	-----	--------------------------------

proval



[FM](#)



For use in hazardous locations Maritime application

[Miscellaneous](#)



[CCC-Ex](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

last modified:

8/22/2025

TURLL

YOUR GLOBAL AUTOMATION PARTNER

6ES7135-4GB01-0AB0

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

sales@turl.com | +852 6339 7344