



spare part SIMATIC DP, electronic module for ET 200SP, F-DI 8x 24 V DC HF, 15 mm width, up to PL e (ISO 13849-1)/ SIL3 (IEC 61508)

General information	
Product type designation	F-DI 8x24VDC HF
usable BaseUnits	BU type A0
Product function	
• I&M data	Yes; I&M0 to I&M3
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	V12
• STEP 7 configurable/integrated from version	V5.5 SP3 / -
• PROFINET from GSD version/GSD revision	V2.31
Operating mode	
• DI	Yes
CiR - Configuration in RUN	
Reparameterization possible in RUN	No
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
power supply according to NEC Class 2 required	No
Input current	
Current consumption (rated value)	75 mA; without load
Current consumption, max.	21 mA; From the backplane bus
Encoder supply	
Number of outputs	8
Short-circuit protection	Yes; Electronic (response threshold 0.7 A to 1.8 A)
Output current	
• up to 60 °C, max.	0.3 A
24 V encoder supply	
• 24 V	Yes; min. L+ (-1.5 V)
• Short-circuit protection	Yes
• Output current, max.	800 mA; Total current of all encoders
Power	
Power consumption from the backplane bus	70 mW
Power loss	
Power loss, typ.	4 W
Address area	
Address space per module	
• Inputs	6 byte
• Outputs	4 byte

Hardware configuration	
Automatic encoding	Yes
<ul style="list-style-type: none"> Electronic coding element type F 	Yes
Digital inputs	
Number of digital inputs	8
Digital inputs, parameterizable	Yes
Sourcing/sinking input	Yes; P-reading
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Input voltage	
<ul style="list-style-type: none"> Rated value (DC) 	24 V
<ul style="list-style-type: none"> for signal "0" 	-30 to +5 V
<ul style="list-style-type: none"> for signal "1" 	+15 to +30 V
Input current	
<ul style="list-style-type: none"> for signal "1", typ. 	3.7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
<ul style="list-style-type: none"> parameterizable 	Yes
<ul style="list-style-type: none"> at "0" to "1", min. 	0.4 ms
<ul style="list-style-type: none"> at "0" to "1", max. 	20 ms
<ul style="list-style-type: none"> at "1" to "0", min. 	0.4 ms
<ul style="list-style-type: none"> at "1" to "0", max. 	20 ms
for technological functions	
<ul style="list-style-type: none"> parameterizable 	No
Cable length	
<ul style="list-style-type: none"> shielded, max. 	1 000 m
<ul style="list-style-type: none"> unshielded, max. 	500 m
Interrupts/diagnostics/status information	
Diagnostics function	Yes; See Chapter "Alarms/diagnostic messages" in the manual
Alarms	
<ul style="list-style-type: none"> Diagnostic alarm 	Yes
<ul style="list-style-type: none"> Hardware interrupt 	No
Diagnostics indication LED	
<ul style="list-style-type: none"> RUN LED 	Yes; green LED
<ul style="list-style-type: none"> ERROR LED 	Yes; red LED
<ul style="list-style-type: none"> Monitoring of the supply voltage (PWR-LED) 	Yes; green PWR LED
<ul style="list-style-type: none"> Channel status display 	Yes; green LED
<ul style="list-style-type: none"> for channel diagnostics 	Yes; red LED
<ul style="list-style-type: none"> for module diagnostics 	Yes; green/red DIAG LED
Potential separation	
Potential separation channels	
<ul style="list-style-type: none"> between the channels 	No
<ul style="list-style-type: none"> between the channels and backplane bus 	Yes
<ul style="list-style-type: none"> between the channels and the power supply of the electronics 	No
Isolation	
Isolation tested with	707 V DC (type test)
Standards, approvals, certificates	
Suitable for safety functions	Yes
Ecological footprint	
<ul style="list-style-type: none"> environmental product declaration 	Yes
Global warming potential	
<ul style="list-style-type: none"> global warming potential, (total) [CO2 eq] 	88.3 kg
<ul style="list-style-type: none"> global warming potential, (during production) [CO2 eq] 	13.1 kg
<ul style="list-style-type: none"> global warming potential, (during operation) [CO2 eq] 	76.6 kg
<ul style="list-style-type: none"> global warming potential, (after end of life cycle) [CO2 eq] 	-1.37 kg
Highest safety class achievable in safety mode	
<ul style="list-style-type: none"> Performance level according to ISO 13849-1 	PLe

• SIL acc. to IEC 61508	SIL 3
Probability of failure (for service life of 20 years and repair time of 100 hours)	
— Low demand mode: PFDavg in accordance with SIL3	< 2.00E-05
— High demand/continuous mode: PFH in accordance with SIL3	< 1.00E-09 1/h

Ambient conditions

Ambient temperature during operation	
• horizontal installation, min.	0 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	0 °C
• vertical installation, max.	50 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	4 000 m; Restrictions for installation altitudes > 2 000 m, see manual

Dimensions

Width	15 mm
Height	73 mm
Depth	58 mm

Weights

Weight, approx.	49 g
-----------------	------

Classifications

	Version	Classification
eClass	14	27-24-26-04
eClass	12	27-24-26-04
eClass	9.1	27-24-26-04
eClass	9	27-24-26-04
eClass	8	27-24-26-04
eClass	7.1	27-24-26-04
eClass	6	27-24-26-04
ETIM	10	EC001599
ETIM	9	EC001599
ETIM	8	EC001599
ETIM	7	EC001599
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval



[Confirmation](#)



[Miscellaneous](#)

General Product Approval	Maritime application	other
--------------------------	----------------------	-------



[Confirmation](#)



Environment

[Environmental Confirmations](#)

[Environmental Confirmations](#)

last modified:

10/23/2025 

TURLL

YOUR GLOBAL AUTOMATION PARTNER

6ES7136-6BA00-0CA0-ET200SP

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

sales@turl.com | +852 6339 7344