

## Data sheet

## 6ES7141-4BH00-0AA0



Figure similar

SIMATIC DP, Electronic module for ET 200 PRO 16 DI 24 V DC, Module diagnostics; incl. bus module, Connection module IO 6ES7194-4CB50-0AA0 order separately

Supply voltage	
Rated value (DC)	24 V
Reverse polarity protection	Yes; Against destruction; encoder power supply outputs applied with reversed polarity
Input current	
from supply voltage 1L+, max.	30 mA
from backplane bus 3.3 V DC, max.	20 mA
Encoder supply	
Number of outputs	8
Short-circuit protection	Yes; per module, electronic
Output current	
• up to 55 °C, max.	1 A
Power loss	
Power loss, typ.	3 W
Address area	
Address space per module	• Address space per module, max. 2 byte
Digital inputs	
Number of digital inputs	16
Sourcing/sinking input	P-reading
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	
all mounting positions	— up to 55 °C, max. 16
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	-3 to +5V
• for signal "1"	+11 to +30V
Input current	
• for signal "1", typ.	4 mA
Input delay (for rated value of input voltage)	
for standard inputs	— parameterizable No
— at "0" to "1", min.	1.2 ms
— at "0" to "1", max.	4.8 ms
— at "1" to "0", min.	0.7 ms
— at "1" to "0", max.	3 ms
Cable length	

• unshielded, max.	30 m
<b>Encoder</b>	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	Yes
<b>Alarms</b>	
• Diagnostic alarm	Yes
<b>Diagnoses</b>	
• Diagnostic information readable	Yes
• Short-circuit	Yes; Sensor supply to M; module by module
<b>Diagnostics indication LED</b>	
• Group error SF (red)	Yes
• Status indicator digital input (green)	Yes; Per channel
<b>Potential separation</b>	
between backplane bus and all other circuit components	Yes
<b>Potential separation digital inputs</b>	
• between the channels	No
• between the channels and backplane bus	Yes
<b>Isolation</b>	
Isolation tested with	707 V DC (type test)
<b>Dimensions</b>	
Width	45 mm
Height	130 mm
Depth	35 mm
<b>Weights</b>	
Weight, approx.	140 g

	Version	Classification
eClass	14	27-24-26-04
eClass	12	27-24-26-04
eClass	9.1	27-24-26-04
eClass	9	27-24-26-04
eClass	8	27-24-26-04
eClass	7.1	27-24-26-04
eClass	6	27-24-26-04
ETIM	10	EC001599
ETIM	9	EC001599
ETIM	8	EC001599
ETIM	7	EC001599
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates		
General Product Approval	EMV	Maritime application



Maritime application	other	Environment
----------------------	-------	-------------



[Confirmation](#)



[Environmental Con-  
firmations](#)



---

last modified:

10/23/2025

# TURLL

YOUR GLOBAL AUTOMATION PARTNER

## 6ES7141-4BH00-0AA0

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

[sales@turl.com](mailto:sales@turl.com) | +852 6339 7344