

Data sheet

6ES7194-6KA00-0XA0

SIMATIC DP, Y cable for ET 200 distributed I/O For double connection of I/Os via single cable to ET 200 5-pole M12, 200mm



Figure similar

General information	
Product type designation	Y cable
Degree and class of protection	
IP degree of protection	IP67
Ambient conditions	
Ambient temperature during assembly, min.	-25 °C
Ambient temperature during assembly, max.	85 °C
Ambient temperature during storage/transportation	
• min.	-50 °C
• max.	80 °C
Cables	
Cable designation	Li9Y11Y 4x 0.34 mm ²
Cable length	0.19 m
Color of core insulation of energy core	white / brown / blue / black
Mechanics/material	
Outgoing feeder type	180° cable outlet
Material of cable sheath	PUR
Material of core insulation	PP
Material property	
• Halogen-free	Yes
• Silicone-free	Yes
Classifications	

	Version	Classification
eClass	14	27-24-22-20
eClass	12	27-24-22-20
eClass	9.1	27-24-22-20
eClass	9	27-24-22-20
eClass	8	27-24-92-05
eClass	7.1	27-24-92-05
eClass	6	27-24-92-05
ETIM	10	EC000237
ETIM	9	EC000237
ETIM	8	EC000237
ETIM	7	EC000237
IDEA	4	3553

UNSPSC

15

32-15-17-03

Approvals / Certificates

General Product Approval



[Manufacturer Declaration](#)



General Product Approval

EMV

Maritime application



last modified:

4/7/2025

TURLL

YOUR GLOBAL AUTOMATION PARTNER

6ES7194-6KA00-0XA0

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

sales@turl.com | +852 6339 7344