



SIMATIC S7-1200, analog I/O SM 1234, 4 AI/2 AO, +/-10 V, 14-bit resolution or 0 (4)-20mA, 13-bit resolution

General information	
Product type designation	SM 1234, AI 4x13 bit/AQ 2x14 bit
Supply voltage	
Rated value (DC)	24 V
Input current	
Current consumption, typ.	60 mA
from backplane bus 5 V DC, typ.	80 mA
Power loss	
Power loss, typ.	2 W
Analog inputs	
Number of analog inputs	4; Current or voltage differential inputs
permissible input voltage for voltage input (destruction limit), max.	35 V
permissible input current for current input (destruction limit), max.	40 mA
Cycle time (all channels) max.	625 μ s
Input ranges	
<ul style="list-style-type: none"> • Voltage • Current • Thermocouple • Resistance thermometer • Resistance 	Yes; ± 10 V, ± 5 V, ± 2.5 V Yes; 4 to 20 mA, 0 to 20 mA No No No
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> • -10 V to +10 V — Input resistance (-10 V to +10 V) • -2.5 V to +2.5 V — Input resistance (-2.5 V to +2.5 V) • -5 V to +5 V — Input resistance (-5 V to +5 V) 	Yes ≥ 9 MOhm Yes ≥ 9 MOhm Yes ≥ 9 MOhm
Input ranges (rated values), currents	
<ul style="list-style-type: none"> • 0 to 20 mA — Input resistance (0 to 20 mA) • 4 mA to 20 mA 	Yes 280 Ω Yes
Analog outputs	
Number of analog outputs	2; Current or voltage
Output ranges, voltage	
<ul style="list-style-type: none"> • -10 V to +10 V 	Yes
Output ranges, current	
<ul style="list-style-type: none"> • 0 to 20 mA • 4 mA to 20 mA 	Yes Yes

Load impedance (in rated range of output)	
<ul style="list-style-type: none"> with voltage outputs, min. with current outputs, max. 	1 000 Ω 600 Ω
Cable length	
<ul style="list-style-type: none"> shielded, max. 	100 m; shielded, twisted pair
Analog value generation for the inputs	
Measurement principle	Differential
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> Resolution with overrange (bit including sign), max. Integration time, parameterizable Interference voltage suppression for interference frequency f1 in Hz 	12 bit; + sign Yes 40 dB, DC to 60 V for interference frequency 50 / 60 Hz
Smoothing of measured values	
<ul style="list-style-type: none"> parameterizable Step: None Step: low Step: Medium Step: High 	Yes Yes Yes Yes Yes
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> Resolution with overrange (bit including sign), max. 	14 bit; Voltage: 14 bit; Current : 13 bit
Errors/accuracies	
Temperature error (relative to input range), (+/-)	25 °C \pm 0.1%, to 55 °C \pm 0.2% total measurement range
Temperature error (relative to output range), (+/-)	25 °C \pm 0.3%, to 55 °C \pm 0.6% total measurement range
Basic error limit (operational limit at 25 °C)	
<ul style="list-style-type: none"> Voltage, relative to input range, (+/-) Current, relative to input range, (+/-) Voltage, relative to output range, (+/-) Current, relative to output range, (+/-) 	0.1 % 0.1 % 0.3 % 0.3 %
Interference voltage suppression for $f = n \times (f1 \pm 1 \%)$, f1 = interference frequency	
<ul style="list-style-type: none"> Common mode voltage, max. 	12 V
Interrupts/diagnostics/status information	
Alarms	Yes
Diagnostics function	Yes
Alarms	
<ul style="list-style-type: none"> Diagnostic alarm 	Yes
Diagnoses	
<ul style="list-style-type: none"> Monitoring the supply voltage Wire-break Short-circuit 	Yes Yes Yes
Diagnostics indication LED	
<ul style="list-style-type: none"> for status of the inputs for status of the outputs for maintenance 	Yes Yes Yes
Potential separation	
Potential separation analog outputs	
<ul style="list-style-type: none"> between the channels and the power supply of the electronics 	No
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
Marine approval	Yes
Ecological footprint	
<ul style="list-style-type: none"> environmental product declaration 	Yes

Global warming potential			
— global warming potential, (total) [CO2 eq]	43.1 kg		
— global warming potential, (during production) [CO2 eq]	7.62 kg		
— global warming potential, (during operation) [CO2 eq]	36 kg		
— global warming potential, (after end of life cycle) [CO2 eq]	-0.544 kg		
Ambient conditions			
Free fall			
• Fall height, max.	0.3 m; five times, in product package		
Ambient temperature during operation			
• min.	-20 °C		
• max.	60 °C		
• horizontal installation, min.	-20 °C		
• horizontal installation, max.	60 °C		
• vertical installation, min.	-20 °C		
• vertical installation, max.	50 °C		
Ambient temperature during storage/transportation			
• min.	-40 °C		
• max.	70 °C		
Air pressure acc. to IEC 60068-2-13			
• Operation, min.	795 hPa		
• Operation, max.	1 080 hPa		
• Storage/transport, min.	660 hPa		
• Storage/transport, max.	1 080 hPa		
Relative humidity			
• Operation at 25 °C without condensation, max.	95 %		
Pollutant concentrations			
• SO2 at RH < 60% without condensation	SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60 % condensation-free		
connection method			
required front connector	Yes		
Mechanics/material			
Enclosure material (front)			
• Plastic	Yes		
Dimensions			
Width	45 mm		
Height	100 mm		
Depth	75 mm		
Weights			
Weight, approx.	220 g		
Classifications			
		Version	Classification
	eClass	14	27-24-22-01
	eClass	12	27-24-22-01
	eClass	9.1	27-24-22-01
	eClass	9	27-24-22-01
	eClass	8	27-24-22-01
	eClass	7.1	27-24-22-01
	eClass	6	27-24-22-01
	ETIM	10	EC001420
	ETIM	9	EC001420
	ETIM	8	EC001420
	ETIM	7	EC001420
	IDEA	4	3562
	UNSPSC	15	32-15-17-05
Approvals / Certificates			
General Product Approval			



[Manufacturer Declaration](#)

[Miscellaneous](#)



[Metrological Approval](#)

General Product Approval	EMV	For use in hazardous locations			
--------------------------	-----	--------------------------------	--	--	--



[EM](#)



For use in hazardous locations	Maritime application				
--------------------------------	----------------------	--	--	--	--



[CCC-Ex](#)



[NK / Nippon Kaiji Kyokai](#)

Maritime application	Environment			
----------------------	-------------	--	--	--



[CCS \(China Classification Society\)](#)



last modified:

5/16/2025

TURLL

YOUR GLOBAL AUTOMATION PARTNER

6ES7234-4HE32-0XB0

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

sales@turl.com | +852 6339 7344