

Data sheet

6ES7288-3AE08-0AA0

SIMATIC S7-200 SMART, Analog input SM AI08, 8 AI, 0...10V, 0...5V, +/-5 V, +/-2.5 V or 0/4-20 mA; 11 bit + sign (12 bit ADC)

General information	
Product type designation	SM AI08, AI 8x12 bit
CiR - Configuration in RUN	
Reparameterization possible in RUN	No
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V; -15 / +20 %
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption, typ.	60 mA
Current consumption, max.	80 mA
from backplane bus 5 V DC, typ.	61 mA
from backplane bus 5 V DC, max.	80 mA
Power loss	
Power loss, typ.	2 W
Analog inputs	
Number of analog inputs	8
Input ranges	
• Voltage	Yes
• Current	Yes
• Thermocouple	No
• Resistance thermometer	No
• Resistance	No
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	12 bit
Dimensions	
Width	45 mm
Height	100 mm
Depth	81 mm
Weights	
Weight, approx.	186 g
Classifications	

	Version	Classification
eClass	14	27-24-22-01
eClass	12	27-24-22-01
eClass	9.1	27-24-22-01
eClass	9	27-24-22-01
eClass	8	27-24-22-01
eClass	7.1	27-24-22-01
eClass	6	27-24-22-01
ETIM	10	EC001420
ETIM	9	EC001420
ETIM	8	EC001420
ETIM	7	EC001420
IDEA	4	3562

UNSPSC

15

32-15-17-05

Approvals / Certificates

General Product Approval



[China RoHS](#)

last modified:

3/12/2024

TURLL

YOUR GLOBAL AUTOMATION PARTNER

6ES7288-3AE08-0AA0

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

sales@turl.com | +852 6339 7344