



Figure similar

\*\*\*spare part\*\*\* SIMATIC S7-300 CPU315F-2 PN/DP, central processing unit with 512 KB work memory, 1st interface MPI/DP 12 Mbps, 2nd interface Ethernet PROFINET, with 2-port switch, Micro Memory Card required

| General information   |  |
|---|--|
| Product type designation                                    | CPU 315F-2 PN/DP                                   |
| HW functional status  | 01   |
| Firmware version  | V3.2   |
| Product function  |  |
| • Isochronous mode  | Yes; Via PROFIBUS DP or PROFINET interface         |
| Engineering with  |  |
| • Programming package                                       | STEP 7 V5.5 or higher, Distributed Safety V5.4 SP4 |
| Supply voltage  |  |
| Rated value (DC)  | 24 V   |
| permissible range, lower limit (DC)                         | 20.4 V   |
| permissible range, upper limit (DC)                         | 28.8 V   |
| external protection for power supply lines (recommendation) | 2 A min.   |
| Mains buffering   |  |
| • Mains/voltage failure stored energy time                  | 5 ms   |
| • Repeat rate, min.   | 1 s  |
| Input current   |  |
| Current consumption (rated value)                           | 750 mA   |
| Current consumption (in no-load operation), typ.            | 150 mA   |
| Inrush current, typ.  | 4 A  |
| I <sup>2</sup> t  | 1 A <sup>2</sup> ·s                                |
| Power loss  |  |
| Power loss, typ.  | 4.65 W   |
| Storage   |  |
| Work memory   |  |
| • integrated  | 512 kbyte  |
| • expandable  | No   |
| Load memory   |  |
| • Plug-in (MMC)   | Yes  |
| • Plug-in (MMC), max.                                       | 8 Mbyte  |
| • Data management on MMC (after last programming), min.     | 10 a   |
| Backup  |  |
| • present   | Yes; Guaranteed by MMC (maintenance-free)          |
| • without battery   | Yes; Program and data                              |
| CPU processing times  |  |
| for bit operations, typ.                                    | 0.05 μs  |
| for word operations, typ.                                   | 0.09 μs  |

|   |   |
|---|---|
| for fixed point arithmetic, typ.                          | 0.12 $\mu$ s  |
| for floating point arithmetic, typ.                       | 0.45 $\mu$ s  |
| <b>CPU-blocks</b>   |   |
| Number of blocks (total)                                  | 1 024; (DBs, FCs, FBs); the maximum number of loadable blocks can be reduced by the MMC used. |
| <b>DB</b>   |   |
| • Number, max.  | 1 024; Number range: 1 to 16000   |
| • Size, max.  | 64 kbyte  |
| <b>FB</b>   |   |
| • Number, max.  | 1 024; Number range: 0 to 7999  |
| • Size, max.  | 64 kbyte  |
| <b>FC</b>   |   |
| • Number, max.  | 1 024; Number range: 0 to 7999  |
| • Size, max.  | 64 kbyte  |
| <b>OB</b>   |   |
| • Size, max.  | 64 kbyte  |
| • Number of free cycle OBs                                | 1; OB 1   |
| • Number of time alarm OBs                                | 1; OB 10  |
| • Number of delay alarm OBs                               | 2; OB 20, 21  |
| • Number of cyclic interrupt OBs                          | 4; OB 32, 33, 34, 35  |
| • Number of process alarm OBs                             | 1; OB 40  |
| • Number of DPV1 alarm OBs                                | 3; OB 55, 56, 57  |
| • Number of isochronous mode OBs                          | 1; OB 61  |
| • Number of startup OBs                                   | 1; OB 100   |
| • Number of asynchronous error OBs                        | 6; OB 80, 82, 83, 85, 86, 87 (OB83 only for PROFINET IO)                                      |
| • Number of synchronous error OBs                         | 2; OB 121, 122  |
| <b>Nesting depth</b>                                      |   |
| • per priority class                                      | 16  |
| • additional within an error OB                           | 4   |
| <b>Counters, timers and their retentivity</b>             |   |
| <b>S7 counter</b>   |   |
| • Number  | 256   |
| <b>Retentivity</b>  |   |
| — can be set  | Yes   |
| — preset  | Z 0 to Z 7  |
| <b>Counting range</b>                                     |   |
| — can be set  | Yes   |
| — lower limit   | 0   |
| — upper limit   | 999   |
| <b>IEC counter</b>  |   |
| • present   | Yes   |
| • Type  | SFB   |
| • Number  | Unlimited (limited only by RAM capacity)  |
| <b>S7 timer</b>   |   |
| • Number  | 256   |
| <b>Retentivity</b>  |   |
| — adjustable  | Yes   |
| — preset  | No retentivity  |
| <b>Time range</b>   |   |
| — lower limit   | 10 ms   |
| — upper limit   | 9 990 s   |
| <b>IEC timer</b>  |   |
| • present   | Yes   |
| • Type  | SFB   |
| • Number  | Unlimited (limited only by RAM capacity)  |
| <b>Data areas and their retentivity</b>                   |   |
| Retentive data area (incl. timers, counters, flags), max. | 128 kbyte   |
| <b>Flag</b>   |   |
| • Size, max.  | 2 048 byte  |

|   |   |
|---|---|
| <ul style="list-style-type: none"> <li>• Retentivity available</li> <li>• Retentivity preset</li> <li>• Number of clock memories</li> </ul>   | Yes; MB 0 to MB 2 047<br>MB 0 to MB 15<br>8; 1 memory byte  |
| <b>Data blocks</b>  |   |
| <ul style="list-style-type: none"> <li>• Retentivity adjustable</li> <li>• Retentivity preset</li> </ul>  | Yes; via non-retain property on DB<br>Yes   |
| <b>Local data</b>   |   |
| <ul style="list-style-type: none"> <li>• per priority class, max.</li> </ul>  | 32 768 byte; Max. 2048 bytes per block  |
| <b>Address area</b>   |   |
| <b>I/O address area</b>   |   |
| <ul style="list-style-type: none"> <li>• Inputs</li> <li>• Outputs</li> </ul>   | 2 048 byte<br>2 048 byte  |
| of which distributed  |   |
| <ul style="list-style-type: none"> <li>— Inputs</li> <li>— Outputs</li> </ul>   | 2 048 byte<br>2 048 byte  |
| <b>Process image</b>  |   |
| <ul style="list-style-type: none"> <li>• Inputs</li> <li>• Outputs</li> <li>• Inputs, adjustable</li> <li>• Outputs, adjustable</li> <li>• Inputs, default</li> <li>• Outputs, default</li> </ul>   | 2 048 byte<br>2 048 byte<br>2 048 byte<br>2 048 byte<br>128 byte<br>128 byte  |
| <b>Subprocess images</b>  |   |
| <ul style="list-style-type: none"> <li>• Number of subprocess images, max.</li> </ul>   | 1; With PROFINET IO, the length of the user data is limited to 1600 bytes   |
| <b>Digital channels</b>   |   |
| <ul style="list-style-type: none"> <li>• Inputs               <ul style="list-style-type: none"> <li>— of which central</li> </ul> </li> <li>• Outputs               <ul style="list-style-type: none"> <li>— of which central</li> </ul> </li> </ul>   | 16 384<br>1 024<br>16 384<br>1 024  |
| <b>Analog channels</b>  |   |
| <ul style="list-style-type: none"> <li>• Inputs               <ul style="list-style-type: none"> <li>— of which central</li> </ul> </li> <li>• Outputs               <ul style="list-style-type: none"> <li>— of which central</li> </ul> </li> </ul>   | 1 024<br>256<br>1 024<br>256  |
| <b>Hardware configuration</b>   |   |
| Number of expansion units, max.   | 3   |
| <b>Number of DP masters</b>   |   |
| <ul style="list-style-type: none"> <li>• integrated</li> <li>• via CP</li> </ul>  | 1<br>4  |
| <b>Number of operable FMs and CPs (recommended)</b>   |   |
| <ul style="list-style-type: none"> <li>• FM</li> <li>• CP, PtP</li> <li>• CP, LAN</li> </ul>  | 8<br>8<br>10  |
| <b>Rack</b>   |   |
| <ul style="list-style-type: none"> <li>• Racks, max.</li> <li>• Modules per rack, max.</li> </ul>   | 4<br>8  |
| <b>Time of day</b>  |   |
| <b>Clock</b>  |   |
| <ul style="list-style-type: none"> <li>• Hardware clock (real-time)</li> <li>• retentive and synchronizable</li> <li>• Backup time</li> <li>• Deviation per day, max.</li> <li>• Behavior of the clock following POWER-ON</li> <li>• Behavior of the clock following expiry of backup period</li> </ul> | Yes<br>Yes<br>6 wk; At 40 °C ambient temperature<br>10 s; Typ.: 2 s<br>Clock continues running after POWER OFF<br>the clock continues at the time of day it had when power was switched off |
| <b>Operating hours counter</b>  |   |
| <ul style="list-style-type: none"> <li>• Number</li> <li>• Number/Number range</li> <li>• Range of values</li> <li>• Granularity</li> </ul>   | 1<br>0<br>0 to 2 <sup>31</sup> hours (when using SFC 101)<br>1 h  |

|  |   |
|--|---|
| <ul style="list-style-type: none"> <li>• retentive</li> </ul>  | Yes; Must be restarted at each restart  |
| <b>Clock synchronization</b>   |   |
| <ul style="list-style-type: none"> <li>• supported</li> </ul>  | Yes   |
| <ul style="list-style-type: none"> <li>• to MPI, master</li> </ul>   | Yes   |
| <ul style="list-style-type: none"> <li>• on MPI, device</li> </ul>   | Yes   |
| <ul style="list-style-type: none"> <li>• to DP, master</li> </ul>  | Yes; With DP slave only slave clock   |
| <ul style="list-style-type: none"> <li>• on DP, device</li> </ul>  | Yes   |
| <ul style="list-style-type: none"> <li>• in AS, master</li> </ul>  | Yes   |
| <ul style="list-style-type: none"> <li>• in AS, device</li> </ul>  | Yes   |
| <ul style="list-style-type: none"> <li>• on Ethernet via NTP</li> </ul>  | Yes; As client  |
| <b>Digital inputs</b>  |   |
| Number of digital inputs   | 0   |
| <b>Digital outputs</b>   |   |
| Number of digital outputs  | 0   |
| <b>Analog inputs</b>   |   |
| Number of analog inputs  | 0   |
| <b>Interfaces</b>  |   |
| Number of PROFINET interfaces  | 1   |
| Number of RS 485 interfaces  | 1   |
| Number of RS 422 interfaces  | 0   |
| <b>1. Interface</b>  |   |
| Interface type   | Integrated RS 485 interface   |
| Isolated   | Yes   |
| <b>Interface types</b>   |   |
| <ul style="list-style-type: none"> <li>• RS 485</li> </ul>   | Yes   |
| <ul style="list-style-type: none"> <li>• Output current of the interface, max.</li> </ul>  | 200 mA  |
| <b>Protocols</b>   |   |
| <ul style="list-style-type: none"> <li>• MPI</li> </ul>  | Yes   |
| <ul style="list-style-type: none"> <li>• PROFIBUS DP master</li> </ul>   | Yes   |
| <ul style="list-style-type: none"> <li>• PROFIBUS DP device</li> </ul>   | Yes   |
| <ul style="list-style-type: none"> <li>• Point-to-point connection</li> </ul>  | No  |
| <b>MPI</b>   |   |
| <ul style="list-style-type: none"> <li>• Transmission rate, max.</li> </ul>  | 12 Mbit/s   |
| <b>Services</b>  |   |
| <ul style="list-style-type: none"> <li>— PG/OP communication</li> </ul>  | Yes   |
| <ul style="list-style-type: none"> <li>— Routing</li> </ul>  | Yes   |
| <ul style="list-style-type: none"> <li>— Global data communication</li> </ul>  | Yes   |
| <ul style="list-style-type: none"> <li>— S7 basic communication</li> </ul>   | Yes   |
| <ul style="list-style-type: none"> <li>— S7 communication</li> </ul>   | Yes   |
| <ul style="list-style-type: none"> <li>— S7 communication, as client</li> </ul>  | No; but via CP and loadable FB  |
| <ul style="list-style-type: none"> <li>— S7 communication, as server</li> </ul>  | Yes   |
| <b>PROFIBUS DP master</b>  |   |
| <ul style="list-style-type: none"> <li>• Transmission rate, max.</li> </ul>  | 12 Mbit/s   |
| <ul style="list-style-type: none"> <li>• max. number of DP devices</li> </ul>  | 124   |
| <b>Services</b>  |   |
| <ul style="list-style-type: none"> <li>— PG/OP communication</li> </ul>  | Yes   |
| <ul style="list-style-type: none"> <li>— Routing</li> </ul>  | Yes   |
| <ul style="list-style-type: none"> <li>— Global data communication</li> </ul>  | No  |
| <ul style="list-style-type: none"> <li>— S7 basic communication</li> </ul>   | Yes; I blocks only  |
| <ul style="list-style-type: none"> <li>— S7 communication</li> </ul>   | Yes   |
| <ul style="list-style-type: none"> <li>— S7 communication, as client</li> </ul>  | No  |
| <ul style="list-style-type: none"> <li>— S7 communication, as server</li> </ul>  | Yes   |
| <ul style="list-style-type: none"> <li>— Equidistance</li> </ul>   | Yes   |
| <ul style="list-style-type: none"> <li>— Isochronous mode</li> </ul>   | Yes; OB 61; isochronous mode can only be used alternatively on PROFIBUS DP or PROFINET IO |
| <ul style="list-style-type: none"> <li>— SYNC/FREEZE</li> </ul>  | Yes   |
| <ul style="list-style-type: none"> <li>— activation/deactivation of DP devices</li> </ul>  | Yes   |
| <ul style="list-style-type: none"> <li>— max. number of DP devices that can be activated/deactivated at the same time</li> </ul> | 8   |

|   |   |
|---|---|
| — Direct data exchange (slave-to-slave communication) | Yes; as subscriber  |
| — DPV1  | Yes   |
| <b>Address area</b>                                   |   |
| — Inputs, max.  | 2 kbyte   |
| — Outputs, max.                                       | 2 kbyte   |
| <b>User data per DP device</b>                        |   |
| — Inputs, max.  | 244 byte  |
| — Outputs, max.                                       | 244 byte  |
| <b>PROFIBUS DP device</b>                             |   |
| • Transmission rate, max.                             | 12 Mbit/s   |
| • automatic baud rate search                          | Yes; only with passive interface  |
| • Address area, max.                                  | 32  |
| • User data per address area, max.                    | 32 byte   |
| <b>Services</b>                                       |   |
| — PG/OP communication                                 | Yes   |
| — Routing   | Yes; Only with active interface   |
| — Global data communication                           | No  |
| — S7 basic communication                              | No  |
| — S7 communication                                    | Yes   |
| — S7 communication, as client                         | No  |
| — S7 communication, as server                         | Yes; Connection configured on one side only   |
| — Direct data exchange (slave-to-slave communication) | Yes   |
| — DPV1  | No  |
| <b>Transfer memory</b>                                |   |
| — Inputs  | 244 byte  |
| — Outputs   | 244 byte  |
| <b>2. Interface</b>                                   |   |
| Interface type  | PROFINET  |
| Isolated  | Yes   |
| automatic detection of transmission rate              | Yes; 10/100 Mbit/s  |
| Autonegotiation                                       | Yes   |
| Autocrossing  | Yes   |
| Change of IP address at runtime, supported            | Yes   |
| <b>Interface types</b>                                |   |
| • RJ 45 (Ethernet)                                    | Yes   |
| • Number of ports                                     | 2   |
| • integrated switch                                   | Yes   |
| <b>Protocols</b>                                      |   |
| • MPI   | No  |
| • PROFINET IO Controller                              | Yes; Also simultaneously with IO-Device functionality                                     |
| • PROFINET IO device                                  | Yes; Also simultaneously with IO Controller functionality                                 |
| • PROFINET CBA  | Yes   |
| • PROFIBUS DP master                                  | No  |
| • PROFIBUS DP device                                  | No  |
| • Open IE communication                               | Yes; Via TCP/IP, ISO on TCP, and UDP  |
| • Web server  | Yes; only read function   |
| • Media redundancy                                    | Yes   |
| <b>PROFINET IO Controller</b>                         |   |
| • Transmission rate, max.                             | 100 Mbit/s  |
| <b>Services</b>                                       |   |
| — PG/OP communication                                 | Yes   |
| — Routing   | Yes   |
| — S7 communication                                    | Yes; With loadable FBs, max. configurable connections: 14, max. number of instances: 32   |
| — Isochronous mode                                    | Yes; OB 61; isochronous mode can only be used alternatively on PROFIBUS DP or PROFINET IO |
| — IRT   | Yes   |
| — Shared device                                       | Yes   |

|   |   |
|---|---|
| — Prioritized startup   | Yes   |
| — Number of IO devices with prioritized startup, max.                         | 32  |
| — Number of connectable IO Devices, max.                                      | 128   |
| — Of which IO devices with IRT, max.  | 64  |
| — of which in line, max.  | 64  |
| — Number of IO Devices with IRT and the option "high flexibility"             | 128   |
| — of which in line, max.  | 61  |
| — Number of connectable IO Devices for RT, max.                               | 128   |
| — of which in line, max.  | 128   |
| — Activation/deactivation of IO Devices                                       | Yes   |
| — Number of IO Devices that can be simultaneously activated/deactivated, max. | 8   |
| — IO Devices changing during operation (partner ports), supported             | Yes   |
| — Number of IO Devices per tool, max.   | 8   |
| — Device replacement without swap medium                                      | Yes   |
| — Send cycles   | 250 µs, 500 µs, 1 ms; 2 ms, 4 ms (not in the case of IRT with "high flexibility" option)                                      |
| — Updating time   | 250 µs to 512 ms (depending on the operating mode, see Manual "S7-300 CPU 31xC and CPU 31x, technical Data" for more details) |
| <b>Address area</b>   |   |
| — Inputs, max.  | 2 kbyte   |
| — Outputs, max.   | 2 kbyte   |
| — User data consistency, max.   | 1 024 byte  |
| <b>PROFINET IO Device</b>   |   |
| <b>Services</b>   |   |
| — PG/OP communication   | Yes   |
| — Routing   | Yes   |
| — S7 communication  | Yes; With loadable FBs, max. configurable connections: 14, max. number of instances: 32                                       |
| — Isochronous mode  | No  |
| — IRT   | Yes   |
| — PROFlenergy   | Yes; With SFB 73 / 74 prepared for loadable PROFlenergy standard FB for I-Device  |
| — Shared device   | Yes   |
| — Number of IO Controllers with shared device, max.                           | 2   |
| <b>Transfer memory</b>  |   |
| — Inputs, max.  | 1 440 byte; Per IO Controller with shared device  |
| — Outputs, max.   | 1 440 byte; Per IO Controller with shared device  |
| <b>Submodules</b>   |   |
| — Number, max.  | 64  |
| — User data per submodule, max.   | 1 024 byte  |
| <b>PROFINET CBA</b>   |   |
| • acyclic transmission  | Yes   |
| • cyclic transmission   | Yes   |
| <b>Open IE communication</b>  |   |
| • Number of connections, max.   | 8   |
| • Local port numbers used at the system end                                   | 0, 20, 21, 23, 25, 80, 102, 135, 161, 443, 8080, 34962, 34963, 34964, 65532, 65533, 65534, 65535                              |
| • Keep-alive function, supported  | Yes   |
| <b>Protocols</b>  |   |
| PROFIsafe   | Yes   |
| <b>Redundancy mode</b>  |   |
| <b>Media redundancy</b>   |   |
| — Switchover time on line break, typ.   | 200 ms; PROFINET MRP  |
| — Number of stations in the ring, max.  | 50  |
| <b>Open IE communication</b>  |   |
| • TCP/IP  | Yes; via integrated PROFINET interface and loadable FBs   |
| — Number of connections, max.   | 8   |
| — Data length for connection type 01H, max.                                   | 1 460 byte  |

|  |   |
|--|---|
| — Data length for connection type 11H, max.                          | 32 768 byte   |
| — several passive connections per port, supported                    | Yes   |
| • ISO-on-TCP (RFC1006)   | Yes; via integrated PROFINET interface and loadable FBs   |
| — Number of connections, max.  | 8   |
| — Data length, max.  | 32 768 byte   |
| • UDP  | Yes; via integrated PROFINET interface and loadable FBs   |
| — Number of connections, max.  | 8   |
| — Data length, max.  | 1 472 byte  |
| <b>Web server</b>  |   |
| • supported  | Yes; only read function   |
| • User-defined websites  | Yes   |
| • Number of HTTP clients   | 5   |
| <b>Communication functions</b>                                       |   |
| PG/OP communication  | Yes   |
| Data record routing  | Yes   |
| <b>Global data communication</b>                                     |   |
| • supported  | Yes   |
| • Number of GD loops, max.   | 8   |
| • Number of GD packets, max.   | 8   |
| • Number of GD packets, transmitter, max.                            | 8   |
| • Number of GD packets, receiver, max.                               | 8   |
| • Size of GD packets, max.   | 22 byte   |
| • Size of GD packet (of which consistent), max.                      | 22 byte   |
| <b>S7 basic communication</b>  |   |
| • supported  | Yes   |
| • User data per job, max.  | 76 byte   |
| • User data per job (of which consistent), max.                      | 76 byte; 76 bytes (with X_SEND or X_RCV); 64 bytes (with X_PUT or X_GET as server)                    |
| <b>S7 communication</b>  |   |
| • supported  | Yes   |
| • as server  | Yes   |
| • as client  | Yes; via integrated PROFINET interface and loadable FB or via CP and loadable FB                      |
| • User data per job, max.  | See online help of STEP 7 (shared parameters of the SFBs/FBs and of the SFCs/FCs of S7 Communication) |
| <b>S5 compatible communication</b>                                   |   |
| • supported  | Yes; via CP and loadable FC   |
| <b>PROFINET CBA (at set setpoint communication load)</b>             |   |
| • Setpoint for the CPU communication load                            | 50 %  |
| • Number of remote interconnection partners                          | 32  |
| • number of master/device functions                                  | 30  |
| • total of all master/device connections                             | 1 000   |
| • data length of all incoming master/device connections, max.        | 4 000 byte  |
| • data length of all outgoing master/device connections, max.        | 4 000 byte  |
| • Number of device-internal and PROFIBUS interconnections            | 500   |
| • Data length of device-internal und PROFIBUS interconnections, max. | 4 000 byte  |
| • Data length per connection, max.                                   | 1 400 byte  |
| <b>Remote interconnections with cyclic transmission</b>              |   |
| — Transmission frequency: Transmission interval, min.                | 10 ms   |
| — Number of incoming interconnections                                | 200   |
| — Number of outgoing interconnections                                | 200   |
| — Data length of all incoming interconnections, max.                 | 2 000 byte  |
| — Data length of all outgoing interconnections, max.                 | 2 000 byte  |
| — Data length per connection, max.                                   | 450 byte  |
| <b>HMI variables via PROFINET (acyclic)</b>                          |   |
| — Number of stations that can log on for HMI variables (PN OPC/iMap) | 3; 2x PN OPC/1x iMap  |

|  |   |
|--|---|
| — HMI variable updating                              | 500 ms  |
| — Number of HMI variables                            | 200   |
| — Data length of all HMI variables, max.             | 2 000 byte  |
| <b>PROFIBUS proxy functionality</b>                  |   |
| — supported  | Yes   |
| — Number of linked PROFIBUS devices                  | 16  |
| — Data length per connection, max.                   | 240 byte; Slave-dependent   |
| <b>Number of connections</b>                         |   |
| • overall  | 16  |
| • usable for PG communication                        | 15  |
| — reserved for PG communication                      | 1   |
| — adjustable for PG communication, min.              | 1   |
| — adjustable for PG communication, max.              | 15  |
| • usable for OP communication                        | 15  |
| — reserved for OP communication                      | 1   |
| — adjustable for OP communication, min.              | 1   |
| — adjustable for OP communication, max.              | 15  |
| • usable for S7 basic communication                  | 14  |
| — reserved for S7 basic communication                | 0   |
| — adjustable for S7 basic communication, min.        | 0   |
| — adjustable for S7 basic communication, max.        | 14  |
| • usable for S7 communication                        | 14  |
| — reserved for S7 communication                      | 0   |
| — adjustable for S7 communication, min.              | 0   |
| — adjustable for S7 communication, max.              | 14  |
| • total number of instances, max.                    | 32  |
| • usable for routing                                 | X1 as MPI: max. 10; X1 as DP master: max. 24; X1 as DP slave (active): max. 14; X2 as PROFINET: 24 max. |
| <b>S7 message functions</b>                          |   |
| Number of login stations for message functions, max. | 16; Depending on the configured connections for PG/OP and S7 basic communication                        |
| Process diagnostic messages                          | Yes   |
| simultaneously active Alarm_S blocks, max.           | 300   |
| <b>Test commissioning functions</b>                  |   |
| Status block   | Yes; Up to 2 simultaneously   |
| Single step  | Yes   |
| Number of breakpoints                                | 4   |
| <b>Status/control</b>                                |   |
| • Status/control variable                            | Yes   |
| • Variables  | Inputs, outputs, memory bits, DB, times, counters   |
| • Number of variables, max.                          | 30  |
| — of which status variables, max.                    | 30  |
| — of which control variables, max.                   | 14  |
| <b>Forcing</b>                                       |   |
| • Forcing  | Yes   |
| • Forcing, variables                                 | Inputs, outputs   |
| • Number of variables, max.                          | 10  |
| <b>Diagnostic buffer</b>                             |   |
| • present  | Yes   |
| • Number of entries, max.                            | 500   |
| — can be set   | No  |
| — of which powerfail-proof                           | 100   |
| • Number of entries readable in RUN, max.            | 499   |
| — can be set   | Yes   |
| — preset   | 10  |
| <b>Service data</b>                                  |   |
| • Can be read out                                    | Yes   |
| <b>Ambient conditions</b>                            |   |
| Ambient temperature during operation                 |   |

- min. 0 °C
- max. 60 °C

**Configuration**

|   |                            |
|---|----------------------------|
| <b>Configuration software</b>                 |                            |
| • STEP 7                                      | Yes; V5.5 or higher        |
| <b>Programming</b>                            |                            |
| • Command set                                 | see instruction list       |
| • Nesting levels                              | 8                          |
| • System functions (SFC)                      | see instruction list       |
| • System function blocks (SFB)                | see instruction list       |
| <b>Programming language</b>                   |                            |
| — LAD   | Yes                        |
| — FBD   | Yes                        |
| — STL   | Yes                        |
| — SCL   | Yes                        |
| — CFC   | Yes                        |
| — GRAPH                                       | Yes                        |
| — HiGraph®                                    | Yes                        |
| <b>Know-how protection</b>                    |                            |
| • User program protection/password protection | Yes                        |
| • Block encryption                            | Yes; With S7 block Privacy |

**Dimensions**

|        |        |
|--------|--------|
| Width  | 40 mm  |
| Height | 125 mm |
| Depth  | 130 mm |

**Weights**

|                 |       |
|-----------------|-------|
| Weight, approx. | 340 g |
|-----------------|-------|

**Classifications**

|        | Version | Classification |
|--------|---------|----------------|
| eClass | 14      | 27-24-22-07    |
| eClass | 12      | 27-24-22-07    |
| eClass | 9.1     | 27-24-22-07    |
| eClass | 9       | 27-24-22-07    |
| eClass | 8       | 27-24-22-07    |
| eClass | 7.1     | 27-24-22-07    |
| eClass | 6       | 27-24-22-07    |
| ETIM   | 10      | EC000236       |
| ETIM   | 9       | EC000236       |
| ETIM   | 8       | EC000236       |
| ETIM   | 7       | EC000236       |
| IDEA   | 4       | 3565           |
| UNSPSC | 15      | 32-15-17-05    |

**Approvals / Certificates**

|                                 |              |
|---------------------------------|--------------|
| <b>General Product Approval</b> | <b>other</b> |
|---------------------------------|--------------|



[Confirmation](#)



[Confirmation](#)

|              |                    |
|--------------|--------------------|
| <b>other</b> | <b>Environment</b> |
|--------------|--------------------|



[Environmental Con-  
firmations](#)

[Environmental Con-  
firmations](#)



---

last modified:

4/7/2025 

# TURLL

YOUR GLOBAL AUTOMATION PARTNER

## 6ES7315-2FJ14-0AB0

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

[sales@turl.com](mailto:sales@turl.com) | +852 6339 7344