

Data sheet

6ES7322-5FF00-0AB0



Figure similar

spare part SIMATIC S7-300, digital output SM 322, isolated, 8 DO, 120/230 V AC, 2 A, with single-point grounding/channel and selectable failure mode, 1x 40-pole

Supply voltage	
Load voltage L1	
• Rated value (AC)	230 V; 120/230 V AC
• permissible range, lower limit (AC)	79 V
• permissible range, upper limit (AC)	264 V
Input current	
from load voltage L1 (without load), max.	2 mA
from backplane bus 5 V DC, max.	100 mA
Power loss	
Power loss, typ.	8.6 W
Digital outputs	
Number of digital outputs	8
Short-circuit protection	Yes; to be provided externally; fuse 3.15 A / 250 V, quick response
Controlling a digital input	Yes
Size of motor starters according to NEMA, max.	Size 5 according to NEMA
Zero-crossing switch	Yes; 60 V
Switching capacity of the outputs	
• on lamp load, max.	50 W
Output voltage	
• for signal "1", min.	L1 (-8.5 V)
Output current	
• for signal "1" rated value	2 A
• for signal "1" permissible range for 0 to 40 °C, min.	10 mA
• for signal "1" permissible range for 0 to 40 °C, max.	2 A
• for signal "1" permissible range for 40 to 60 °C, min.	10 mA
• for signal "1" permissible range for 40 to 60 °C, max.	1 A
• for signal "1" minimum load current	10 mA
• for signal "1" permissible surge current, max.	20 A; with 2 half waves
• for signal "0" residual current, max.	2 mA
Parallel switching of two outputs	
• for uprating	No
• for redundant control of a load	Yes
Switching frequency	
• with resistive load, max.	10 Hz
• with inductive load, max.	0.5 Hz
• with inductive load (acc. to IEC 60947-5-1, AC15), max.	0.5 Hz
• on lamp load, max.	1 Hz
Total current of the outputs (per group)	

horizontal installation	
— up to 40 °C, max.	8 A
— up to 60 °C, max.	4 A
vertical installation	
— up to 40 °C, max.	4 A
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Interrupts/diagnostics/status information	
Diagnostics function	Yes; Parameterizable
Alarms	
• Diagnostic alarm	Yes; Parameterizable
Diagnostics indication LED	
• Group error SF (red)	Yes
• Status indicator digital output (green)	Yes
Potential separation	
Potential separation digital outputs	
• between the channels	Yes
• between the channels, in groups of	1
• between the channels and backplane bus	Yes; Optocoupler
Isolation	
Isolation tested with	1 500 V AC
Connection method	
required front connector	40-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	275 g
Classifications	

	Version	Classification
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	10	EC001419
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates	
General Product Approval	



[Manufacturer Declaration](#)

[Miscellaneous](#)



General Product Approval	EMV
--------------------------	-----



[Manufacturer Declaration](#)

[China RoHS](#)



For use in hazardous locations	Maritime application
--------------------------------	----------------------

[EM](#)



[NK / Nippon Kaiji Kyokai](#)



last modified:

4/7/2025

TURLL

YOUR GLOBAL AUTOMATION PARTNER

6ES7322-5FF00-0AB0

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

sales@turl.com | +852 6339 7344