



spare part SIMATIC S7-300, front connector with screw connections, 40-pole

General information	
Product type designation	Front connector
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	60 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Accessories	
belongs to product	S7-300
Connection method	
Connection I/O signals	
• Connection method	Screw terminals
• Number of lines per connection	1; Or 2 cables up to 0.75 mm² (total) in a shared end sleeve
Conductor cross-section in mm²	
— Connectable cable cross-sections for massive cables, min.	0.14 mm²
— Connectable cable cross-sections for massive cables, min.	0.75 mm²
— Connectable cable cross-sections for flexible cables without end sleeve, min.	0.14 mm²
— Connectable cable cross-sections for flexible cables without end sleeve, max.	0.75 mm²
— Connectable cable cross-sections for flexible cables with end sleeve, min.	0.14 mm²
— Connectable cable cross-sections for flexible cables with end sleeve, max.	0.75 mm²
Conductor cross-section acc. to AWG	
— Connectable cable cross-sections for massive cables, min.	24
— Connectable cable cross-sections for massive cables, min.	19
— Connectable cable cross-sections for flexible cables without end sleeve, min.	24
— Connectable cable cross-sections for flexible cables without end sleeve, max.	19
— Connectable cable cross-sections for flexible cables with end sleeve, min.	24
— Connectable cable cross-sections for flexible cables with end sleeve, max.	19
Wire end processing	

— Stripped length of cables, min.	6 mm
— Stripped length of cables, max.	6 mm
— End sleeve acc. to DIN 46228 without plastic sleeve	Design A, 5 mm to 7 mm long
— End sleeve acc. to DIN 46228 with plastic sleeve	Design E, up to 6 mm long
Mounting	
— Tool	Screwdriver, conical design, 3 mm to 3.5 mm
— Tightening torque, min.	0.4 N·m
— Tightening torque, max.	0.7 N·m
Dimensions	
Width	21.6 mm
Height	125 mm
Depth	40.9 mm
Weights	
Weight, approx.	137 g
Classifications	

	Version	Classification
eClass	14	27-24-22-92
eClass	12	27-24-22-92
eClass	9.1	27-24-22-92
eClass	9	27-24-22-92
eClass	8	27-24-92-90
eClass	7.1	27-24-92-90
eClass	6	27-24-92-90
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates
General Product Approval



[Confirmation](#)



Test Certificates	other	Environment			
Special Test Certificate	Confirmation		Miscellaneous	Environmental Confirmations	Environmental Confirmations

last modified: 4/7/2025 

TURLL

YOUR GLOBAL AUTOMATION PARTNER

6ES7392-1AM00-0AA0

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

CHECK STOCK & PRICE



Need Assistance? Scan to Chat on WhatsApp

sales@turll.com | +852 6339 7344