

## Data sheet

## 6ES7403-1TA11-0AA0

SIMATIC S7-400, ext. rack ER1 aluminum, with 18 slots, for signal modules, 2 redundant PS can be plugged in



Figure similar

General information		
Product type designation	ER1	
Hardware configuration		
Rack		
• Communication bus	No	
• P bus	Yes	
Slots		
• Number of slots	18	
Standards, approvals, certificates		
CE mark	Yes	
UL approval	Yes	
FM approval	Yes	
RCM (formerly C-TICK)	Yes	
KC approval	Yes	
EAC (formerly Gost-R)	Yes	
Ambient conditions		
Ambient temperature during operation		
• min.	0 °C	
• max.	60 °C	
Ambient temperature during storage/transportation		
• min.	0 °C	
• max.	70 °C	
Dimensions		
Width	482.5 mm	
Height	290 mm	
Depth	27.5 mm	
Weights		
Weight, approx.	2 500 g	
Classifications		
	<b>Version</b>	<b>Classification</b>
eClass	14	27-24-22-03
eClass	12	27-24-22-03
eClass	9.1	27-24-22-03
eClass	9	27-24-22-03
eClass	8	27-24-22-03
eClass	7.1	27-24-22-03

eClass	6	27-24-22-03
ETIM	10	EC000810
ETIM	9	EC000810
ETIM	8	EC000810
ETIM	7	EC000810
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvals / Certificates

General Product Approval



[Miscellaneous](#)



General Product Approval

EMV

For use in hazardous locations

[China RoHS](#)

[Miscellaneous](#)

[Manufacturer Declaration](#)



For use in hazardous locations



[Declaration of Conformity](#)

[FM](#)



[Type Examination Certificate](#)

For use in hazardous locations

Maritime application



[NK / Nippon Kaiji Kyokai](#)



Maritime application

Environment



[CCS \(China Classification Society\)](#)



last modified:

6/7/2025

# TURLL

YOUR GLOBAL AUTOMATION PARTNER

## 6ES7403-1TA11-0AA0

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

sales@turl.com | +852 6339 7344