



SIMATIC S7-400, analog input SM 431, isolated 8 AI, resolution 14 bit, U/IResistor 8 AI, cycle time 0.416 ms

Figure similar

Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V; Only required for supplying 2-wire transmitters
<ul style="list-style-type: none"> <li>Reverse polarity protection</li> </ul>	Yes
Input current	
from load voltage L+ (without load), max.	200 mA; for 8 connected, fully controlled 2-wire transmitters
from backplane bus 5 V DC, max.	1 000 mA
Power loss	
Power loss, typ.	4.9 W
Analog inputs	
Number of analog inputs	8
<ul style="list-style-type: none"> <li>For voltage/current measurement</li> </ul>	8
<ul style="list-style-type: none"> <li>For resistance measurement</li> </ul>	4
permissible input voltage for voltage input (destruction limit), max.	18 V; 18 V continuous, 75 V for 1 ms (mark to space ratio 1:20)
permissible input current for current input (destruction limit), max.	40 mA; Permanent
Constant measurement current for resistance-type transmitter, typ.	1.67 mA
Input ranges	
<ul style="list-style-type: none"> <li>Voltage</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Current</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Thermocouple</li> </ul>	No
<ul style="list-style-type: none"> <li>Resistance thermometer</li> </ul>	No
<ul style="list-style-type: none"> <li>Resistance</li> </ul>	Yes
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> <li>1 V to 5 V</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (1 V to 5 V)</li> </ul>	10 MΩ
<ul style="list-style-type: none"> <li>-1 V to +1 V</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (-1 V to +1 V)</li> </ul>	10 MΩ
<ul style="list-style-type: none"> <li>-10 V to +10 V</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (-10 V to +10 V)</li> </ul>	100 kΩ
Input ranges (rated values), currents	
<ul style="list-style-type: none"> <li>-20 mA to +20 mA</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (-20 mA to +20 mA)</li> </ul>	50 Ω
<ul style="list-style-type: none"> <li>4 mA to 20 mA</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (4 mA to 20 mA)</li> </ul>	50 kΩ
Input ranges (rated values), resistors	
<ul style="list-style-type: none"> <li>0 to 600 ohms</li> </ul>	Yes

<b>Cable length</b>		
• shielded, max.	200 m	
<b>Analog value generation for the inputs</b>		
<b>Integration and conversion time/resolution per channel</b>		
• Resolution with overrange (bit including sign), max.	14 bit; 14 / 14 / 14	
• Integration time, parameterizable	Yes	
• Basic conversion time (ms)	52 $\mu$ s	
• Interference voltage suppression for interference frequency f1 in Hz	none / 400 / 60 / 50 Hz	
• Time constant of the input filter	15 $\mu$ s	
• Basic execution time of the module (all channels released)	0.42 ms	
<b>Encoder</b>		
<b>Connection of signal encoders</b>		
• for voltage measurement	Yes; possible	
• for current measurement as 2-wire transducer	Yes	
• for current measurement as 4-wire transducer	Yes	
• for resistance measurement with two-wire connection	Yes; Line resistances are also measured	
• for resistance measurement with three-wire connection	Yes; Line resistances are also measured	
• for resistance measurement with four-wire connection	Yes	
<b>Errors/accuracies</b>		
Temperature error (relative to input range), (+/-)	0.03 %/K	
<b>Operational error limit in overall temperature range</b>		
• Voltage, relative to input range, (+/-)	0.7 %; $\pm 0.7$ % at $\pm 1$ V; $\pm 0.9$ % at $\pm 10$ V, 1 to 5 V	
• Current, relative to input range, (+/-)	0.8 %; at $\pm 20$ mA, 4 to 20 mA	
• Resistance, relative to input range, (+/-)	1 %	
<b>Basic error limit (operational limit at 25 °C)</b>		
• Voltage, relative to input range, (+/-)	0.6 %; 0.6 % at $\pm 1$ V; 0.75 % at $\pm 10$ V, 1 to 5 V	
• Current, relative to input range, (+/-)	0.7 %; at $\pm 20$ mA, 4 to 20 mA	
• Resistance, relative to input range, (+/-)	0.7 %; 0 to 600 ohms	
<b>Interrupts/diagnostics/status information</b>		
Diagnostics function	No	
<b>Potential separation</b>		
<b>Potential separation analog inputs</b>		
• Potential separation analog inputs	Yes; internal/external	
• between the channels	No	
• between the channels and backplane bus	Yes	
• Between the channels and load voltage L+	Yes	
<b>Isolation</b>		
Isolation tested with	2 120 V DC between bus and analog section; 500 V DC between bus and local ground; 500 V DC between analog part and L+/M; 2 120 V DC between analog part and local ground; 2 120 V DC between L+/M and local ground	
<b>Dimensions</b>		
Width	25 mm	
Height	290 mm	
Depth	210 mm	
<b>Weights</b>		
Weight, approx.	500 g	
<b>Classifications</b>		
	<b>Version</b>	<b>Classification</b>
eClass	16	27-24-22-01
eClass	14	27-24-22-01
eClass	12	27-24-22-01
eClass	9.1	27-24-22-01
eClass	9	27-24-22-01
eClass	8	27-24-22-01
eClass	7.1	27-24-22-01
eClass	6	27-24-22-01

ETIM	10	EC001420
ETIM	9	EC001420
ETIM	8	EC001420
ETIM	7	EC001420
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval



[Miscellaneous](#)



[Metrological Approval](#)



General Product Approval

EMV



[China RoHS](#)

[Miscellaneous](#)

[Manufacturer Declaration](#)



For use in hazardous locations



[FM](#)



[Type Examination Certificate](#)

For use in hazardous locations

Maritime application



[NK / Nippon Kaiji Kyokai](#)

Maritime application



[CCS \(China Classification Society\)](#)

last modified:

6/7/2025

# TURLL

YOUR GLOBAL AUTOMATION PARTNER

## 6ES7431-1KF20-0AB0

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

sales@turl.com | +852 6339 7344