



SIMATIC S7-400, analog input SM 431, isolated 16 AI; resolution 16 bit, U/I/Resistor/Thermocouple/Pt100 , alarm, diagnostics

Figure similar

Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V; Only required for supplying 2-wire transmitters
<ul style="list-style-type: none"> <li>Reverse polarity protection</li> </ul>	Yes
Input current	
from load voltage L+ (without load), max.	400 mA; for 16 connected, fully controlled 2-wire transmitters
from backplane bus 5 V DC, max.	700 mA
Power loss	
Power loss, typ.	4.5 W
Analog inputs	
Number of analog inputs	16
<ul style="list-style-type: none"> <li>For voltage/current measurement</li> </ul>	16
<ul style="list-style-type: none"> <li>For resistance measurement</li> </ul>	8
permissible input voltage for voltage input (destruction limit), max.	18 V; 18 V continuous, 75 V for 1 ms (mark to space ratio 1:20)
permissible input current for current input (destruction limit), max.	40 mA
Constant measurement current for resistance-type transmitter, typ.	1.67 mA
Input ranges	
<ul style="list-style-type: none"> <li>Voltage</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Current</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Thermocouple</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Resistance thermometer</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Resistance</li> </ul>	Yes
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> <li>1 V to 5 V</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (1 V to 5 V)</li> </ul>	1 M $\Omega$
<ul style="list-style-type: none"> <li>-1 V to +1 V</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (-1 V to +1 V)</li> </ul>	1 M $\Omega$
<ul style="list-style-type: none"> <li>-10 V to +10 V</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (-10 V to +10 V)</li> </ul>	1 M $\Omega$
<ul style="list-style-type: none"> <li>-2.5 V to +2.5 V</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (-2.5 V to +2.5 V)</li> </ul>	1 M $\Omega$
<ul style="list-style-type: none"> <li>-25 mV to +25 mV</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (-25 mV to +25 mV)</li> </ul>	1 M $\Omega$
<ul style="list-style-type: none"> <li>-250 mV to +250 mV</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (-250 mV to +250 mV)</li> </ul>	1 M $\Omega$
<ul style="list-style-type: none"> <li>-5 V to +5 V</li> </ul>	Yes

— Input resistance (-5 V to +5 V)	1 M $\Omega$
• -50 mV to +50 mV	Yes
— Input resistance (-50 mV to +50 mV)	1 M $\Omega$
• -500 mV to +500 mV	Yes
— Input resistance (-500 mV to +500 mV)	1 M $\Omega$
• -80 mV to +80 mV	Yes
— Input resistance (-80 mV to +80 mV)	1 M $\Omega$
<b>Input ranges (rated values), currents</b>	
• 0 to 20 mA	Yes
— Input resistance (0 to 20 mA)	50 $\Omega$
• -10 mA to +10 mA	Yes
— Input resistance (-10 mA to +10 mA)	50 $\Omega$
• -20 mA to +20 mA	Yes
— Input resistance (-20 mA to +20 mA)	50 $\Omega$
• 4 mA to 20 mA	Yes
— Input resistance (4 mA to 20 mA)	50 $\Omega$
• -5 mA to +5 mA	Yes
— Input resistance (-5 mA to +5 mA)	50 $\Omega$
<b>Input ranges (rated values), thermocouples</b>	
• type B	Yes
— Input resistance (Type B)	1 M $\Omega$
• Type E	Yes
— Input resistance (Type E)	1 M $\Omega$
• Type J	Yes
— Input resistance (type J)	1 M $\Omega$
• Type K	Yes
— Input resistance (Type K)	1 M $\Omega$
• Type L	Yes
— Input resistance (Type L)	1 M $\Omega$
• Type N	Yes
— Input resistance (Type N)	1 M $\Omega$
• Type R	Yes
— Input resistance (Type R)	1 M $\Omega$
• Type S	Yes
— Input resistance (Type S)	1 M $\Omega$
• Type T	Yes
— Input resistance (Type T)	1 M $\Omega$
• Type U	Yes
— Input resistance (Type U)	1 M $\Omega$
<b>Input ranges (rated values), resistance thermometer</b>	
• Ni 100	Yes
— Input resistance (Ni 100)	1 M $\Omega$
• Ni 1000	Yes
— Input resistance (Ni 1000)	1 M $\Omega$
• Pt 100	Yes
— Input resistance (Pt 100)	1 M $\Omega$
• Pt 1000	Yes
— Input resistance (Pt 1000)	1 M $\Omega$
• Pt 200	Yes
— Input resistance (Pt 200)	1 M $\Omega$
• Pt 500	Yes
— Input resistance (Pt 500)	1 M $\Omega$
<b>Input ranges (rated values), resistors</b>	
• 0 to 48 ohms	Yes
— Input resistance (0 to 48 ohms)	1 M $\Omega$
• 0 to 150 ohms	Yes
— Input resistance (0 to 150 ohms)	1 M $\Omega$
• 0 to 300 ohms	Yes
— Input resistance (0 to 300 ohms)	1 M $\Omega$


<ul style="list-style-type: none"> <li>• 0 to 600 ohms <ul style="list-style-type: none"> <li>— Input resistance (0 to 600 ohms)</li> </ul> </li> <li>• 0 to 6000 ohms <ul style="list-style-type: none"> <li>— Input resistance (0 to 6000 ohms)</li> </ul> </li> </ul>	<p>Yes</p> <p>1 M<math>\Omega</math></p> <p>Yes; Usable up to 5000 Ohm</p> <p>1 M<math>\Omega</math></p>
<b>Thermocouple (TC)</b>	
Temperature compensation	
<ul style="list-style-type: none"> <li>— Parameterizable</li> <li>— external temperature compensation with Pt100</li> <li>— external temperature compensation with compensations socket</li> <li>— dynamic reference temperature value</li> </ul>	<p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p>
<b>Characteristic linearization</b>	
<ul style="list-style-type: none"> <li>• Parameterizable <ul style="list-style-type: none"> <li>— for thermocouples</li> <li>— for resistance thermometer</li> </ul> </li> </ul>	<p>Yes</p> <p>Type B, E, J, K, L, N, R, S, T, U</p> <p>Pt100, Pt200, Pt500, Pt1000, Ni100, Ni1000</p>
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>• shielded, max.</li> </ul>	200 m; 50 m with thermocouples and input ranges $\leq$ 80 mV
<b>Analog value generation for the inputs</b>	
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> <li>• Resolution with overrange (bit including sign), max.</li> <li>• Integration time, parameterizable</li> <li>• Basic conversion time (ms)</li> <li>• Integration time (ms)</li> <li>• Interference voltage suppression for interference frequency f1 in Hz</li> </ul>	<p>16 bit; 16 / 16 / 16</p> <p>Yes</p> <p>6 / 20,1 / 23,5 ms</p> <p>2,5 / 16,7 / 20 ms</p> <p>400 / 60 / 50 Hz</p>
<b>Encoder</b>	
Connection of signal encoders	
<ul style="list-style-type: none"> <li>• for voltage measurement</li> <li>• for current measurement as 2-wire transducer</li> <li>• for current measurement as 4-wire transducer</li> <li>• for resistance measurement with two-wire connection</li> <li>• for resistance measurement with three-wire connection</li> <li>• for resistance measurement with four-wire connection</li> </ul>	<p>Yes; possible</p> <p>Yes</p> <p>Yes</p> <p>Yes; Line resistances are also measured</p> <p>Yes</p> <p>Yes</p>
<b>Errors/accuracies</b>	
Temperature error (relative to input range), (+/-)	0.004 %/K
Operational error limit in overall temperature range	
<ul style="list-style-type: none"> <li>• Voltage, relative to input range, (+/-)</li> <li>• Current, relative to input range, (+/-)</li> <li>• Resistance, relative to input range, (+/-)</li> <li>• Resistance thermometer, relative to input range, (+/-)</li> <li>• Thermocouple, relative to input range, (+/-)</li> </ul>	<p>0.3 %; <math>\pm 0.3</math> % at <math>\pm 250</math> mV, <math>\pm 500</math> mV, <math>\pm 1</math> V, <math>\pm 2.5</math> V, <math>\pm 5</math> V, 1 to 5 V, <math>\pm 10</math> V; <math>\pm 0.31</math> % at <math>\pm 80</math> mV; <math>\pm 0.32</math> % at <math>\pm 50</math> mV; <math>\pm 0.35</math> % at <math>\pm 25</math> mV</p> <p>0.3 %; at 0 to 20 mA, <math>\pm 5</math> mA, <math>\pm 10</math> mA, <math>\pm 20</math> mA, 4 to 20 mA</p> <p>0.3 %; <math>\pm 0.3</math> % at 0 to 48 Ohm (4-conductor measurement), 0 to 150 Ohm (4-conductor measurement), 0 to 300 Ohm (4-conductor measurement), 0 to 5000 Ohm (4-conductor measurement, in range of 6000 Ohm); <math>\pm 0.4</math> % at 0 to 300 Ohm (3-conductor measurement), 0 to 600 Ohm (3-conductor measurement), 0 to 5000 Ohm (3-conductor measurement, in range of 6000 Ohm);</p> <p>0.4 %</p> <p>TC Type B (<math>\pm 11.5</math> K), TC Type R (<math>\pm 7.3</math> K), TC Type S (<math>\pm 8.3</math> K), TC Type T (<math>\pm 1.7</math> K), TC Type E (<math>\pm 3.2</math> K), TC Type J (<math>\pm 4.3</math> K), TC Type K (<math>\pm 6.2</math> K), TC Type U (<math>\pm 2.8</math> K), TC Type L (<math>\pm 4.2</math> K), TC Type N (<math>\pm 4.4</math> K)</p>
Basic error limit (operational limit at 25 °C)	
<ul style="list-style-type: none"> <li>• Voltage, relative to input range, (+/-)</li> <li>• Current, relative to input range, (+/-)</li> <li>• Resistance, relative to input range, (+/-)</li> <li>• Resistance thermometer, relative to input range, (+/-)</li> <li>• Thermocouple, relative to input range, (+/-)</li> </ul>	<p>0.15 %; <math>\pm 0.15</math> % at <math>\pm 250</math> mV, <math>\pm 500</math> mV, <math>\pm 1</math> V, <math>\pm 2.5</math> V, <math>\pm 5</math> V, 1 V to 5 V, <math>\pm 10</math> V; <math>\pm 0.17</math> % at <math>\pm 80</math> mV; <math>\pm 0.19</math> % at <math>\pm 50</math> mV; <math>\pm 0.23</math> % at <math>\pm 25</math> mV</p> <p>0.15 %; at 0 to 20 mA, <math>\pm 5</math> mA, <math>\pm 10</math> mA, <math>\pm 20</math> mA, 4 to 20 mA</p> <p>0.15 %; <math>\pm 0.15</math> % at 0 to 48 ohms (4-conductor measurement), 0 to 150 ohms (4-conductor measurement), 0 to 300 ohms (4-conductor measurement), 0 to 5000 ohms (4-conductor measurement, in range of 6000 ohms); <math>\pm 0.3</math> % at 0 to 300 ohms (3-conductor measurement), 0 to 600 ohms (3-conductor measurement), 0 to 5000 ohms (3-conductor measurement, in range of 6000 ohms)</p> <p>0.3 %</p> <p>TC Type B (<math>\pm 7.6</math> K), TC Type R (<math>\pm 4.8</math> K), TC Type S (<math>\pm 5.4</math> K), TC Type T (<math>\pm 1.1</math> K), TC Type E (<math>\pm 1.8</math> K), TC Type J (<math>\pm 2.3</math> K), TC Type K (<math>\pm 3.4</math> K), TC Type U (<math>\pm 1.7</math> K), TC Type L (<math>\pm 2.3</math> K), TC Type N (<math>\pm 2.6</math> K)</p>
<b>Interrupts/diagnostics/status information</b>	

Diagnosics function	Yes; Parameterizable
<b>Alarms</b>	
• Diagnostic alarm	Yes; Parameterizable
• Limit value alarm	Yes; Parameterizable
• Hardware interrupt	Yes; Parameterizable
<b>Diagnoses</b>	
• Diagnostic information readable	Yes
<b>Diagnosics indication LED</b>	
• internal fault INTF (red)	Yes
• external fault EXTF (red)	Yes
<b>Potential separation</b>	
<b>Potential separation analog inputs</b>	
• Potential separation analog inputs	Yes; internal/external
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes
<b>Isolation</b>	
Isolation tested with	2 120 V DC between bus and L+/M; 2 120 V DC between bus and analog section; 500 V DC between bus and local ground; 500 V DC between analog section and L+/M; 2 120 V DC between analog section and local ground; 2 120 V DC between L+/M and local ground
<b>Dimensions</b>	
Width	25 mm
Height	290 mm
Depth	210 mm
<b>Weights</b>	
Weight, approx.	500 g


	Version	Classification
eClass	14	27-24-22-01
eClass	12	27-24-22-01
eClass	9.1	27-24-22-01
eClass	9	27-24-22-01
eClass	8	27-24-22-01
eClass	7.1	27-24-22-01
eClass	6	27-24-22-01
ETIM	10	EC001420
ETIM	9	EC001420
ETIM	8	EC001420
ETIM	7	EC001420
IDEA	4	3562
UNSPSC	15	32-15-17-05

**Approvals / Certificates**

**General Product Approval**




EG-Konf.




[Manufacturer Declaration](#)

[Miscellaneous](#)




UL



**General Product Approval** **EMV**


[Metrological Approval](#)




RCM

[China RoHS](#)

[Miscellaneous](#)



RCM



RCM

For use in hazardous locations



FM



[Type Examination Certificate](#)

For use in hazardous locations

Maritime application



[NK / Nippon Kaiji Kyokai](#)

Maritime application



[CCS \(China Classification Society\)](#)

last modified:

6/7/2025

# TURLL

YOUR GLOBAL AUTOMATION PARTNER

## 6ES7431-7QH00-0AB0

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

sales@turl.com | +852 6339 7344