

Data sheet

6ES7460-0AA01-0AB0



SIMATIC S7-400, interface module Send IM 460-0 for central coupling without PS transfer, with C-bus

Figure similar

Input current			
from backplane bus 5 V DC, max.		140 mA	
Power loss			
Power loss, max.		700 mW	
Hardware configuration			
Cable length between first and last interface module, max.		5 m	
Connection method			
termination plug		6ES7461-0AA0-7AA0	
Dimensions			
Width		25 mm	
Height		290 mm	
Depth		280 mm	
Weights			
Weight, approx.		600 g	
Classifications			
		Version	Classification
	eClass	14	27-24-22-08
	eClass	12	27-24-22-08
	eClass	9.1	27-24-22-08
	eClass	9	27-24-22-08
	eClass	8	27-24-22-08
	eClass	7.1	27-24-22-08
	eClass	6	27-24-22-08
	ETIM	10	EC001423
	ETIM	9	EC001423
	ETIM	8	EC001423
	ETIM	7	EC001423
	IDEA	4	3564
	UNSPSC	15	32-15-17-05
Approvals / Certificates			
General Product Approval			

[Miscellaneous](#)



General Product Approval	EMV	For use in hazardous locations
--------------------------	-----	--------------------------------


[China RoHS](#)

[Miscellaneous](#)



For use in hazardous locations	Maritime application
--------------------------------	----------------------


[FM](#)



Maritime application



Maritime application



last modified: 6/7/2025

TURLL

YOUR GLOBAL AUTOMATION PARTNER

6ES7460-0AA01-0AB0

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

CHECK STOCK & PRICE



Need Assistance? Scan to Chat on WhatsApp

sales@turll.com | +852 6339 7344