

## Data sheet

## 6ES7461-3AA01-0AA0



SIMATIC S7-400, interface module receiver IM 461-3 for distributed coupling up to 102 m, with C-bus

Figure similar

Input current			
from backplane bus 5 V DC, max.	620 mA		
Power loss			
Power loss, max.	3 100 mW		
Hardware configuration			
Cable length between first and last interface module, max.	102.25 m		
Connection method			
termination plug	6ES7461-3AA0-7AA1		
Dimensions			
Width	25 mm		
Height	290 mm		
Depth	280 mm		
Weights			
Weight, approx.	620 g		
Classifications			
		<b>Version</b>	<b>Classification</b>
eClass		14	27-24-22-08
eClass		12	27-24-22-08
eClass		9.1	27-24-22-08
eClass		9	27-24-22-08
eClass		8	27-24-22-08
eClass		7.1	27-24-22-08
eClass		6	27-24-22-08
ETIM		10	EC001423
ETIM		9	EC001423
ETIM		8	EC001423
ETIM		7	EC001423
IDEA		4	3564
UNSPSC		15	32-15-17-05
Approvals / Certificates			
General Product Approval			



[Miscellaneous](#)



General Product Approval

EMV

For use in hazardous locations

[China RoHS](#)

[Miscellaneous](#)



For use in hazardous locations

Maritime application

[EM](#)



[Type Examination Certificate](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



Maritime application



[CCS \(China Classification Society\)](#)

last modified:

6/7/2025

# TURLL

YOUR GLOBAL AUTOMATION PARTNER

## 6ES7461-3AA01-0AA0

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

[sales@turl.com](mailto:sales@turl.com) | +852 6339 7344