

Data sheet

6GK7177-1MA20-0AA0



LOGO! CSM12/24 Compact Switch Module connection of a LOGO! (. ..0BA7/...0BA8) and up to 3 further nodes to Ind. Ethernet with 10/100 Mbit/s Unmanaged switch, 4 RJ45 ports, 1x front port for diagnostics DC 12/24V power supply LED diagnostics, LOGO! setup.

product type designation	
product brand name	LOGO!
product type designation	CSM 12/24
Technical Product Detail Page	https://i.siemens.com/1P6GK7177-1MA20-0AA0
transfer rate	
transfer rate	10, 100 Mbit/s
interfaces / for communication / integrated	
number of electrical connections	
• for network components or terminal equipment	4
number of 100 Mbit/s SC ports	
• for multimode	0
interfaces / other	
number of electrical connections	
• for power supply	1
type of electrical connection	
• for power supply	3-pole terminal block
supply voltage, current consumption, power loss	
type of voltage / 1 / of the supply voltage	
• supply voltage / 1 / rated value	24 V
• power loss [W] / 1 / rated value	1.5 W
• supply voltage / 1 / voltage range	10.2 ... 30.2
• consumed current / 1 / maximum	0.15 A
• type of electrical connection / 1 / for power supply	3-pole terminal block
• product component / 1 / fusing at power supply input	Yes
ambient conditions	
ambient temperature	
• during operation	0 ... 55 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
relative humidity	
• at 25 °C / without condensation / during operation / maximum	90 %
protection class IP	IP20
design, dimensions and weights	
design	LOGO! module
width	71.5 mm
height	90 mm
depth	58.2 mm
net weight	0.15 kg

fastening method	
<ul style="list-style-type: none"> • 35 mm DIN-rail mounting 	Yes
<ul style="list-style-type: none"> • wall mounting 	Yes
<ul style="list-style-type: none"> • S7-300 rail mounting 	No
<ul style="list-style-type: none"> • S7-1500 rail mounting 	No
product functions / management, configuration, engineering	
product function	
<ul style="list-style-type: none"> • multiport mirroring 	No
<ul style="list-style-type: none"> • switch-managed 	No
standards, specifications, approvals	
certificate of suitability	
<ul style="list-style-type: none"> • CE marking 	Yes
<ul style="list-style-type: none"> • cULus approval 	Yes
<ul style="list-style-type: none"> • KC approval 	No
<ul style="list-style-type: none"> • Regulatory Compliance Mark (RCM) 	Yes
standard	
<ul style="list-style-type: none"> • for immunity to EMC 	EN 61000-6-2
<ul style="list-style-type: none"> • for safety / from CSA and UL 	UL 508, CSA C22.2 No. 142
standards, specifications, approvals / hazardous environments	
certificate of suitability	
<ul style="list-style-type: none"> • ATEX 	Yes
<ul style="list-style-type: none"> • UKEX 	Yes
<ul style="list-style-type: none"> • IECEx 	Yes
<ul style="list-style-type: none"> • ULhazloc approval 	Yes
<ul style="list-style-type: none"> • CCC / for hazardous zone according to GB standard 	Yes
<ul style="list-style-type: none"> • FM registration 	Yes
standards, specifications, approvals / other	
certificate of suitability	
<ul style="list-style-type: none"> • RoHS conformity 	Yes
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
<ul style="list-style-type: none"> • total 	57.94 kg
<ul style="list-style-type: none"> • during manufacturing 	7.42 kg
<ul style="list-style-type: none"> • during operation 	50.38 kg
<ul style="list-style-type: none"> • after end of life 	0.14 kg
further information / internet links	
internet link	
<ul style="list-style-type: none"> • to website: Selection guide for cables and connectors 	https://support.industry.siemens.com/cs/ww/en/view/109766358
<ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool 	https://www.siemens.com/tstcloud
<ul style="list-style-type: none"> • to website: Industrial communication 	https://www.siemens.com/simatic-net
<ul style="list-style-type: none"> • to web page: SiePortal 	https://sieportal.siemens.com/
<ul style="list-style-type: none"> • to website: Image database 	https://www.automation.siemens.com/bilddb
<ul style="list-style-type: none"> • to website: CAx-Download-Manager 	https://www.siemens.com/cax
<ul style="list-style-type: none"> • to website: Industry Online Support 	https://support.industry.siemens.com
security information	
security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase</p>

customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Approvals / Certificates

General Product Approval



EG-Konf.

[Declaration of Conformity](#)



CCC



[China RoHS](#)



UL

General Product Approval

For use in hazardous locations

Environment



RCM



IECEX



ATEX

[EM](#)

[CCC-Ex](#)



EPD

last modified:

12/15/2025

TURLL

YOUR GLOBAL AUTOMATION PARTNER

6GK7177-1MA20-0AA0

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

CHECK STOCK & PRICE



Need Assistance? Scan to Chat on WhatsApp

sales@turl.com | +852 6339 7344