

Data sheet for SINAMICS V90

Article No. : 6SL3210-5FE11-0UA0



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data

Input

Number of phases	3 AC
Line voltage	380 ... 480 V +10 % -15 %
Line frequency	45 ... 66 Hz

Output

Rated power	1.00 kW
Rated current (IN)	3.00 A
Max. output current	9.00 A

Inputs / outputs

Standard digital inputs

Number	10
--------	----

Digital outputs

Number	6
--------	---

Analog inputs

Number	2
--------	---

Analog outputs

Number	2
--------	---

Mechanical data

Degree of protection	IP20 / UL open type
Frame size	FSA
Net weight	1.85 kg
Width	80.0 mm
Height	180.0 mm
Depth	200.0 mm

Ambient conditions

Cooling	natural convection
Installation altitude	1,000 m

Ambient temperature

Operation	0 ... 45 °C
Storage	-40 ... 70 °C

Relative humidity

Max. operation	90 %
----------------	------

Standards

Compliance with standards	CE, KC, cULus, EAC, C-Tick (RCM)
---------------------------	----------------------------------

Communication

Communication	USS, Modbus RTU
---------------	-----------------

TURLL

YOUR GLOBAL AUTOMATION PARTNER

6SL3210-5FE11-0UA0

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

sales@turl.com | +852 6339 7344