

Data sheet for SINAMICS V90

Article No. : 6SL3210-5FE13-5UA0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :



Figure similar

Rated data

Input

Number of phases	3 AC
Line voltage	380 ... 480 V +10 % -15 %
Line frequency	45 ... 66 Hz

Output

Rated power	3.50 kW
Rated current (IN)	11.00 A
Max. output current	33.00 A

Inputs / outputs

Standard digital inputs

Number	10
--------	----

Digital outputs

Number	6
--------	---

Analog inputs

Number	2
--------	---

Analog outputs

Number	2
--------	---

Mechanical data

Degree of protection	IP20 / UL open type
Frame size	FSC
Net weight	5.65 kg
Width	140.0 mm
Height	260.0 mm
Depth	240.0 mm

Ambient conditions

Cooling	Fan
Installation altitude	1,000 m

Ambient temperature

Operation	0 ... 45 °C
Storage	-40 ... 70 °C

Relative humidity

Max. operation	90 %
----------------	------

Standards

Compliance with standards	CE, KC, cULus, EAC, C-Tick (RCM)
---------------------------	----------------------------------

Communication

Communication	USS, Modbus RTU
---------------	-----------------

TURLL

YOUR GLOBAL AUTOMATION PARTNER

6SL3210-5FE13-5UA0

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

CHECK STOCK & PRICE



Need Assistance? Scan to Chat on WhatsApp

sales@turll.com | +852 6339 7344