

## Data sheet for SIMOTICS S-1FK7



Figure similar

Article No. : 1FK7062-2AF71-1RA2

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

Rated speed (100 K)	3,000 rpm
Number of poles	8
Rated torque (100 K)	6.0 Nm
Rated current	4.0 A
Static torque (60 K)	7.10 Nm
Static torque (100 K)	8.50 Nm
Stall current (60 K)	4.30 A
Stall current (100 K)	5.30 A
Moment of inertia	11.200 kgcm <sup>2</sup>
Efficiency	91.0 %

### Physical constants

Torque constant	1.60 Nm/A
Voltage constant at 20° C	102.5 V/1000*min <sup>-1</sup>
Winding resistance at 20° C	1.15 Ω
Rotating field inductance	14.6 mH
Electrical time constant	12.80 ms
Mechanical time constant	1.49 ms
Thermal time constant	35 min
Shaft torsional stiffness	37,000 Nm/rad
Net weight of the motor	9.1 kg

### Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	63
Cooling	Natural cooling
Radial runout tolerance	0.040 mm
Concentricity tolerance	0.10 mm
Axial runout tolerance	0.10 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP65 and DE flange IP67
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	Standard (Anthracite RAL 7016)
Holding brake	without holding brake
Shaft end	Feather key
Encoder system	Encoder AM20DQI: absolute encoder 20 bits (resolution 1048576, encoder-internal 512 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)

### Optimum operating point

Optimum speed	3,000 rpm
Optimum power	1.9 kW

### Limiting data

Max. permissible speed (mech.)	7,200 rpm
Max. permissible speed (inverter)	5,600 rpm
Maximum torque	26.0 Nm
Maximum current	19.2 A

### Recommended Motor Module

Rated inverter current	5 A
Maximum inverter current	15 A
Maximum torque	22.10 Nm

# TURLL

YOUR GLOBAL AUTOMATION PARTNER

## 1FK7062-2AF71-1RA2

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

[sales@turl.com](mailto:sales@turl.com) | +852 6339 7344