



Pneumatic Time-Relay block on-delay 10...180 s 1NO + 1NC for 3RT6 motor contactors size S0

product category	Pneumatic delay blocks
product designation	Pneumatic valve block
General technical data	
certificate of suitability	CE / CCC
size of contactor	S0
insulation voltage with degree of pollution 3 at AC rated value	690 V
protection class IP on the front	IP20
mechanical service life (operating cycles) typical	3 000 000
mechanical service life (operating cycles)	
• with 3RT2.2 contactor	3 000 000
electrical endurance (operating cycles) at AC-15 at 230 V typical	200 000
adjustable pickup delay time	10 ... 180 s
relative accuracy of the operating delay time/backslide delay time	10 %
active principle	pneumatic
Substance Prohibittance (Date)	05/01/2012
Net Weight	74 g
Switching Function	
switching function	
• ON-delay	Yes
• OFF delay	No
number of NC contacts delayed switching	1
number of NO contacts delayed switching	1
operational current at AC-15	
• at 500 V rated value	2.5 A
• at 690 V rated value	1.5 A
operational current of auxiliary contacts at AC-14	
• at 230 V	6 A
• at 400 V	4 A
• at 500 V	2.5 A
operational current of auxiliary contacts at AC-12 maximum	10 A
operational current of auxiliary contacts at AC-15	
• at 230 V	6 A
• at 400 V	4 A
operational current of auxiliary contacts at DC-13	
• at 24 V	4 A
• at 48 V	2 A
• at 110 V	0.7 A
• at 220 V	0.3 A

- at 440 V

0.15 A

Ambient conditions**ambient temperature**

- during operation -25 ... +60 °C
- during storage -50 ... +80 °C

Electrical Safety**touch protection against electrical shock** finger-safe**Short-circuit protection**design of the fuse link for short-circuit protection of the auxiliary switch required Fuse gG 10 A with short-circuit current I_k = 1 kA according to IEC 60947-5-1**Installation/ mounting/ dimensions****mounting position** any**fastening method** clip-on**height** 45 mm**width** 45 mm**depth** 60 mm**Connections/ Terminals**

type of electrical connection for auxiliary and control circuit screw-type terminals

connectable conductor cross-section for auxiliary contacts

- solid or stranded 0.5 ... 2.5 mm²
- finely stranded with core end processing 0.5 ... 2.5 mm²

type of connectable conductor cross-sections

- for auxiliary contacts
 - solid 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²)
 - finely stranded with core end processing 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²)
- for AWG cables for auxiliary contacts 2x (18 ... 14), 2x (20 ... 16)

AWG number as coded connectable conductor cross section for auxiliary contacts 20 ... 14**Approvals Certificates**

General Product Approval

EMV

other

[Confirmation](#)**Environment**[Environmental Confirmations](#)**Further information****Information on the packaging**<https://support.industry.siemens.com/cs/ww/en/view/109813875>**Information for data generation and storage**<https://support.industry.siemens.com/cs/ww/en/view/109995012>**Information- and Downloadcenter (Catalogs, Brochures,...)**<https://www.siemens.com/ic10>**Industry Mall (Online ordering system)**<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT6926-2PA11>**Cax online generator**<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT6926-2PA11>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<https://support.industry.siemens.com/cs/ww/en/ps/3RT6926-2PA11>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT6926-2PA11&lang=en



last modified:

4/3/2025 

TURLL

YOUR GLOBAL AUTOMATION PARTNER

3RT6926-2PA11-TIME

OFFICIAL DATASHEET & QUOTATION

- 100% New & Original Factory Sealed
- Global Express Shipping (DHL/FedEx/UPS)
- 12-Month Warranty Protection
- Professional Technical Support

[CHECK STOCK & PRICE](#)



Need Assistance? Scan to Chat on WhatsApp

sales@turl.com | +852 6339 7344